

Part number		LVDS-FI-S20S-DF11-20DS-300			
Type		Customer LVDS cable CON1= FI-S20S CON2= DF11-20DS-2C length= 300 mm			
Length		300 mm			
Connector 1		FI-S20S			
Connector 2		DF11-20DS-2C			
Connector 1		Connector 2			
FI-S20S		DF11-20DS-2C			
1	3V3 LCD	1	3V3 LCD	3V3 LCD	2
2	3V3 LCD	3	GND	GND	4
3	GND	5	LCD DATA0 P	LCD DATA1 P	6
4	GND	7	LCD DATA0 N	LCD DATA1 N	8
5	LCD DATA0 N	9	GND	GND	10
6	LCD DATA0 P	11	LCD DATA2 P	LCD DATA3 P	12
7	GND	13	LCD DATA2 N	LCD DATA3 N	14
8	LCD DATA1 N	15	GND	GND	16
9	LCD DATA1 P	17	LCD DCLK P	LCD MODE	18
10	GND	19	LCD DCLK N	LCD SCAN DIR	20
11	LCD DATA2 N				
12	LCD DATA2 P				
13	GND				
14	LCD DCLK N				
15	LCD DCLK P				
16	GND				
17	LCD DATA3 N				
18	LCD DATA3 P				
19	LCD MODE				
20	LCD SCAN DIR				

For following wire should use twisted pair

(+3V3_LCD, +3V3_LCD), (GND, GND),
(LCD_DATAx_P, LCD_DATAx_N),
(LCD_DCLK_P, LCD_DCLK_N),
(LCD_MODE, LCD_SCAN_DIR)

