



SPECIFICATION:
 Contact Resistance: 30m ohm max.
 30m ohm max.
 Insulator Resistance:
 1000m ohm min. at dc 500v
 Current Rating:
 1 AMP
 Dielectric Withstanding Voltage:
 AC 500V For 1 minute
 Operating Temperature:
 -55°C ~+105°C
 Contact Material:
 Brass
 Insulator Material:
 PBT & 30% Glass Fiber UL 94V-0

Position	A	B	C	D	E
10	10.16	18.00	23.00	23.00	19.72
14	15.24	23.08	28.08	28.08	24.80
16	17.78	25.62	30.62	30.62	27.34
20	22.86	30.70	35.70	35.70	32.42
24	27.94	35.78	40.78	40.78	37.50
26	30.48	38.32	43.32	43.32	40.04
30	35.56	43.40	48.40	48.40	45.12
34	40.64	48.48	53.48	53.48	50.20
40	48.26	56.10	61.10	61.10	57.82
50	60.96	68.80	73.80	73.80	70.52
60	73.66	81.50	86.50	86.50	83.22
64	78.74	86.68	91.58	91.58	88.30

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel		TOLERANCE 容許公差 .0 ± .00 ± ANG. ±	PART NAME 品名 BOX HEADER IDC TYPE 2.54mm X 2.54mm 2XXXP WITHOUT S/R WITHOUT EAR SELECTIVE GOLD PLATING GREY COLOR ROHS LOW-LEAD
DWG. 製圖 Yumi	SCALE 比例 參考	UNIT 單位 MM	PART NO. 料號 C3501-XXNNSG00R
DATE 制表日 2009/12/22	PAGE 張數 1 OF 1	REV. 版次 A	