






ALLYSTAR GNSS MODULES

Model	Physical		Grade	GNSS							Accuracy			Features						Interface				
	Image	Size (mm)	Standard Professional Automotive	Band	GPS	BDS	GLONASS	Galileo	QZSS	IRNSS	Meter	Sub-Meter	Centi-Meter	Build-in LNA	Data Logging	Programmable(Flash)	D-GNSS	RAW Data	RTK Rover	Dead Reckoning	USB	UART	I2C	SPI
TAU1103		10*10	•	L1	•	•			•		•		•	•	•	•					•	•		
TAU1105			•	L1	•	•	•	•	•			•		•	•	•	•					•	•	
TAU1111		12*16	•	L1	•	•	•	•	•		•		•	•	•	•				•	•	•	•	
TAU1201		12*16	•	L1/L5	•	•	•	•	•		•		•	•	•	•	•	• ^[1]			•	•	•	•
TAU1204			•	L1/L5	•	•		•	•	•		•		•	•	•	•					•	•	•
TAU1202		10*10	•	L1/L5	•	•	•	•	•		•		•	•	•	•					•	•		
TAU1205			•	L1/L5	•	•		•	•	•		•		•	•	•	•					•	•	
TAU1302		12*16	•	L1/L2/L5/L6	•	•	•	•	•			•		•	•	•	•			•	•	•	•	

2020.12.23 updated

* [1] Customized firmware supports GNSS raw data output.