



Product Specification

AU OPTRONICS CORPORATION

(v) Preliminary Specifications

() Final Specifications

Module	21.3 Inch Color TFT-LCD
Model Name	G213UAN01.0

Customer	Date
_____	_____
Checked & Approved by	Date
_____	_____
Customer's sign back page	



Approved by	Date
<i>Jason Pan</i>	<u>2022/08/03</u>
Prepared by	Date
<i>Livia Huang</i>	<u>2022/08/03</u>
General Display Business Division / AU Optronics corporation	



Contents

1. Operating Precautions	4
2. General Description	5
2.1 Display Characteristics	5
2.2 Optical Characteristics	6
3. Functional Block Diagram	9
4. Absolute Maximum Ratings	10
4.1 Absolute Ratings of TFT LCD Module	10
4.2 Absolute Ratings of Environment	10
5. Electrical Characteristics	11
5.1 TFT LCD Module	11
5.2 Backlight Unit	13
6. Signal Characteristic	15
6.1 Pixel Format Image	15
6.2 LVDS Data Format	16
6.3 Signal Description	17
6.4 Interface Timing	18
6.5 Power ON/OFF Sequence	20
7. Reliability Test Criteria	21
8. Mechanical Characteristics	22
8.1 LCM Outline Dimension	23
9. Label and Packaging	24
9.1 Shipping Label (on the rear side of TFT-LCD display)	24
9.2 Carton Package	25
10 Safety	26
10.1 Sharp Edge Requirements	
10.2 Materials	
10.3 Capacitors	
10.4 National Test Lab Requirement	

Record of Revision

Version	Date (yyyy/m/d)	Page	Old description	New Description
0.1	2022/03/24	All	first edition	
0.2	2022/04/22	4	ESD (Electro Static "Discharge")	ESD (Electro Static "Discharge")
		6	White Luminance / Conditions ILED="100mA"(center point)	White Luminance / Conditions ILED="70mA"(center point)"
		20	Note 3-6: Voltage of "VDO"	Note 3-6: Voltage of"VDD"
		15	Pixel Format Image 	Pixel Format Image 
		5	Weight 2800typ	Weight 2300typ
03	2022.07.29	6	Uniformity:80% min	Add 85% typ
04	2022/08/03	5	BLU Power:16.9W(max)	BLU Power:16.1W(max), Total:26.2 (Max)
		6	ILED=100mA(center point)	ILED=70mA(center point)
		14	Backlight connector: CI1408M1HRL-NH	Backlight connector CI1408M1HRN-NH



1. Operating Precautions

- 1) Since front polarizer is easily damaged, please be cautious and not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or soft cloth.
- 5) Since the panel is made of glass, it may be broken or cracked if dropped or bumped on hard surface.
- 6) To avoid ESD (Electro Static Discharge) damage, be sure to ground yourself before handling TFT-LCD Module.
- 7) Do not open nor modify the module assembly.
- 8) Do not press the reflector sheet at the back of the module to any direction.
- 9) In case if a module has to be put back into the packing container slot after it was taken out from the container, do not press the center of the LED light bar edge. Instead, press at the far ends of the LED light bar edge softly. Otherwise the TFT Module may be damaged.
- 10) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) TFT-LCD Module is not allowed to be twisted & bent even force is added on module in a very short time. Please design your display product well to avoid external force applying to module by end-user directly.
- 12) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 13) Severe temperature condition may result in different luminance, response time and lamp ignition voltage.
- 14) Continuous operating TFT-LCD display under low temperature environment may accelerate lamp exhaustion and reduce luminance dramatically.
- 15) The data on this specification sheet is applicable when LCD module is placed in landscape position.
- 16) Continuous displaying fixed pattern may induce image sticking. It's recommended to use screen saver or shuffle content periodically if fixed pattern is displayed on the screen.



Product Specification

AU OPTRONICS CORPORATION

2. General Description

G213UAN01.0 is a Color Active Matrix Liquid Crystal Display composed of a TFT-LCD panel and a backlight system. The screen format is intended to support the UXGA (1600(H) x 1200(V)) screen and 16.7M colors. All input signals are 2-channel LVDS interface compatible.

2.1 Display Characteristics

The following items are characteristics summary on the table under 25 °C condition:

Items	Unit	Specifications
Screen Diagonal	[inch]	21.3"
Active Area	[mm]	432.0 x 324.0
Resolution		1600(x3) x 1200
Pixel Pitch	[mm]	0.270 (H) × 0.270 (V)
Pixel Arrangement		R.G.B. Vertical Stripe
Display Mode		AHVA
Nominal Input Voltage VDD	[Volt]	12V
Power Consumption	[Watt]	Total:26.2 (Max) LCD module:10.1W (white pattern) BLU: 16.1W
Weight	[Grams]	2300g (typ.)
Physical Size	[mm]	456.0 (H) x 349.5 (V) x 17.6 (D) (Typ)
Electrical Interface		LVDS
Surface Treatment		Anti-Glare
Support Color		16.7 M Colors ,True 8 Bit (RGB)
Temperature Range Operating Storage (Non-Operating)	[°C] [°C]	0 to +50 -20 to +60
RoHS Compliance		RoHS Compliance


2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25 °C (Room Temperature):


Item	Unit	Conditions	Min.	Typ.	Max.	Note	
White Luminance	cd/m ²	I _{LED} =70mA(center point)	400	500	-		
Uniformity	%	9 points	80	85	-		
Contrast Ratio	--		1260	1800		4	
Response Time	msec	Rising		10	20	5	
		Falling		10	20		
		Rising + Falling		20	40		
Viewing Angle	degree	Horizontal CR >= 10	(Right)	85	89	-	6
			(Left)	85	89	-	
		Vertical CR >= 10	(Upper)	85	89	-	
			(Lower)	85	89	-	
Color / Chromaticity Coordinates (CIE 1931)	--	Red x	(0.626)	(0.656)	(0.686)		
		Red y	(0.300)	(0.330)	(0.360)		
		Green x	(0.285)	(0.315)	(0.345)		
		Green y	(0.610)	(0.640)	(0.670)		
		Blue x	(0.120)	(0.150)	(0.180)		
		Blue y	(0.029)	(0.059)	(0.089)		
		White x	0.269	0.299	0.329		
		White y	0.285	0.315	0.345		
Color Gamut	%	sRGB		100%			

Note 1: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring (at surface 35°C). In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room.



Note 2: Definition of 9 points position



Note 3: Definition of luminance uniformity of 9 points.


$$\delta w_9 = \frac{\text{Minimum Brightness of nine points}}{\text{Maximum Brightness of nine points}}$$

Note 4: Definition of contrast ratio (CR):

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$


Note 5: Definition of response time:

The output signals of photo detector are measured when the input signals are changed from "White" to "Black" (falling time) and from "Black" to "White" (rising time), respectively. The response time interval is between 10% and 90% of amplitudes. Please refer to the figure as below.




Note 6: Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as below: 90° (θ) horizontal left and right, and 90° (ϕ) vertical high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated to its center to develop the desired measurement viewing angle.



3. Functional Block Diagram

The following diagram shows the functional block of the 21.3 inch color TFT/LCD module:



AUO Display Plus Confidential

4. Absolute Maximum Ratings


4.1 Absolute Ratings of TFT LCD Module

Item	Symbol	Min	Max	Unit
VDD	Power Supply Input Voltage	10.8	13.2	[Volt]

4.2 Absolute Ratings of Environment

Item	Symbol	Min	Max	Unit
Operating Temperature	TOP	0	+50	[°C]
Operation Humidity	HOP	5	90	[%RH]
Storage Temperature	TST	-20	+60	[°C]
Storage Humidity	HST	5	90	[%RH]


Note: Maximum Wet-Bulb should be 39 °C and no condensation.



Operating Range



Storage Range



5. Electrical Characteristics



5.1 TFT LCD Module

5.1.1 Power Specification

Input power specifications are shown as follows;

Symbol	Parameter	Min	Typ	Max	Units	Remark
VDD	Power supply Input voltage	10.8	12	13.2	[Volt]	±10%
IDD	Power supply Input Current (RMS)		0.7	0.84	[A]	Vin=12V, White Pattern, at 60Hz
IRush	Inrush Current			5	[A]	Note 1
PDD	VDD Power Consumption		8.4	10.1	[Watt]	Vin=12V, White Pattern, at 60Hz
VDDrp	Allowable VDD Ripple Voltage			500	[mV] p-p	With panel loading

Note 1: Measurement condition:




5.1.2 LVDS DC Signal Electrical Characteristics

a. Input signals shall be low or Hi-Z state when VDD is off.


Note: LVDS Signal Waveform.

Symbol	Item	Min.	Typ.	Max.	Unit	Remark
V _{TH}	Differential Input High Threshold	-	-	+100	[mV]	V _{CM} =1.2V
V _{TL}	Differential Input Low Threshold	-100	-	-	[mV]	V _{CM} =1.2V
VID	Input Differential Voltage	100	-	600	[mV]	
V _{ICM}	Differential Input Common Mode Voltage	+1.0	+1.2	+1.5	[V]	V _{TH} /V _{TL} =±200mV

Single-end Signal



Differential Signal



Note: AC Characteristics


Symbol	Description	Min	Max	Unit	Remark
F _{DEV}	Maximum deviation of input clock frequency during Spread Spectrum	-	± 3	%	
F _{MOD}	Maximum modulation frequency of input clock during Spread Spectrum	-	200	KHz	

Note: F_{clk}- LVDS Clock Frequency.



Product Specification

AU OPTRONICS CORPORATION



AUO Display Plus Confidential for Promate Use Only



5.2 Backlight Unit

5.2.1 LED Backlight Unit : Light bar Connector

Connector Name / Designation	LED Connector
Manufacturer	Cvilux
Backlight connector	CI1408M1HRN-NH
Mating connector	CI1408SL000-NH

5.2.2 Pin Assignment

Pin #	Symbol	Description
1	Ch1	IRLED (current out)
2	Ch2	IRLED (current out)
3	Ch3	IRLED (current out)
4	V _{SLED}	VLED (voltage in)
5	V _{SLED}	VLED (voltage in)
6	Ch4	IRLED (current out)
7	Ch5	IRLED (current out)
8	Ch6	IRLED (current out)



LB connector

5.2.3 Parameter guideline for LED

Following characteristics are measured under a stable condition using an inverter at 25°C (Room Temperature):

Symbol	Parameter	Min.	Typ.	Max.	Unit	Remark
I_L	LED Supply Current	-	70	-	[mA]	Ta = 25°C,
V_L	LED Supply Voltage	-	37.05	38.22	[Volt]	I _F = 70mA, Ta = 25°C
P_{BLU}	LED Power Consumption	-	15.561	16.1	[Watt]	I _F = 70mA, Ta = 25°C
L_L	LED Life Time	50,000	-	-	Hrs	I _F = mA, Ta = 25°C

Note 1: Ta means ambient temperature of TFT-LCD module.

Note 2: I_L , V_L are defined for one channel LED. There are 6 LED channel in back light unit.

Note 3: LED light bar is 78 LEDs (6 strings, 13pcs for each string)

Note 4: There are one light bar in back light unit.

Note 5: The voltage capacity of LED driver IC must be over max. of LED Voltage.

Note 6: Definition of life time: Brightness becomes to 50% of its original value.


Note 7: If module is driven by high current or at high ambient temperature & humidity condition. The operating life will reduce.

Note 8: Recommendation for LED driver power design – Due to there are electrical property deviation in LED and monitor set system component after long time operation, AUO strongly recommend the design value of LED driver board OVP (Over Voltage Protection) should be 10% higher than max value of LED string voltage (Vs) at least.


6. Signal Characteristic

6.1 Pixel Format Image

Following figure shows the relationship between the input signals and LCD pixel format.



6.2 LVDS Data Format



8 Bit Color Bit Order			
MSB	R7	G7	B7
	R6	G6	B6
	R5	G5	B5
	R4	G4	B4
	R3	G3	B3
	R2	G2	B2
	R1	G1	B1
LSB	R0	G0	B0

Note1: Normally DE mode only. VS and HS on EVEN channel are not used.

Note2: Please follow VESA.

Note3: 8-bits signal input

6.3 Signal Description

6.3.1 TFT LCD Module: LVDS Connector

TFT-LCD Connector	Manufacturer	JAE	
	Part Number	FI-XB30SSLA-HF15	
Mating Connector	Manufacturer	JAE	STM
	Part Number	JAE_FI-X30H	STM_PFSKX10001N30A

6.3.2 Connector Pin Assignment

■ LVDS CN1

PIN #	Symbol	Description	Remark
1	RxO0-	Negative LVDS differential data input (Odd data)	
2	RxO0+	Positive LVDS differential data input (Odd data)	
3	RxO1-	Negative LVDS differential data input (Odd data)	
4	RxO1+	Positive LVDS differential data input (Odd data)	
5	RxO2-	Negative LVDS differential data input (Odd data)	
6	RxO2+	Positive LVDS differential data input (Odd data)	
7	GND	Ground	
8	RxOCLK-	Negative LVDS differential clock input (Odd clock)	
9	RxOCLK+	Positive LVDS differential clock input (Odd clock)	
10	RxO3-	Negative LVDS differential data input (Odd data)	
11	RxO3+	Positive LVDS differential data input (Odd data)	
12	RxE0-	Negative LVDS differential data input (Even data)	
13	RxE0+	Positive LVDS differential data input (Even data)	
14	GND	Ground	
15	RxE1-	Negative LVDS differential data input (Even data)	
16	RxE1+	Positive LVDS differential data input (Even data)	
17	GND	Ground	
18	RxE2-	Negative LVDS differential data input (Even data)	
19	RxE2+	Positive LVDS differential data input (Even data)	
20	RxECLK-	Negative LVDS differential clock input (Even clock)	
21	RxECLK+	Positive LVDS differential clock input (Even clock)	
22	RxE3-	Negative LVDS differential data input (Even data)	
23	RxE3+	Positive LVDS differential data input (Even data)	
24	GND	Must Connect to GND	
25	NC	No connection (for AUO test only. Do not connect)	
26	NC	No connection (for AUO test only. Do not connect)	
27	NC	No connection (for AUO test only. Do not connect)	
28	VDD	Power Supply Input Voltage	
29	VDD	Power Supply Input Voltage	



Product Specification

AU OPTRONICS CORPORATION

30	VDD	Power Supply Input Voltage	
----	-----	----------------------------	--

6.4 Interface Timing

6.4.1 Timing Characteristics

It only support DE mode and the input timing are shown as the following table.

Symbol	Description		Min.	Typ.	Max.	Unit	Remark
Tv	Vertical Section	Period	1229	1233	-	Th	
Tdisp (v)		Active	1200			Th	
Tblk (v)		Blanking	29	33	-	Th	
Fv		Frequency	58.5	60.0	61.5	Hz	
Th	Horizontal Section	Period	850	880	940	Tclk	
Tdisp (h)		Active	800			Tclk	
Tblk (h)		Blanking	50	80	140	Tclk	
Fh		Frequency	71.5	74.0	78.0	KHz	Note 3-3
Tclk	LVDS Clock	Period	14.81	15.36	16.13	ns	1/Fclk
Fclk		Frequency	62.0	65.1	67.5	MHz	Note 3-4

Note 3-3: The equation is listed as following. Please don't exceed the above recommended value.

$$Fh (\text{Min.}) = Fclk (\text{Min.}) / Th (\text{Min.});$$

$$Fh (\text{Typ.}) = Fclk (\text{Typ.}) / Th (\text{Typ.});$$

$$Fh (\text{Max.}) = Fclk (\text{Max.}) / Th (\text{Min.});$$


Note 3-4: The equation is listed as following. Please don't exceed the above recommended value.

$$Fclk (\text{Min.}) = Fv (\text{Min.}) \times Th (\text{Min.}) \times Tv (\text{Min.});$$

$$Fclk (\text{Typ.}) = Fv (\text{Typ.}) \times Th (\text{Typ.}) \times Tv (\text{Typ.});$$


$$Fclk (\text{Max.}) = Fv (\text{Max.}) \times Th (\text{Typ.}) \times Tv (\text{Typ.});$$

6.4.2 Input Timing Diagram



6.5 Power ON/OFF Sequence

VDD power, LVDS signal and backlight on/off sequence are as following. LVDS signals from any system shall be Hi-Z state when VDD is off.



Power Sequence Timing

Symbol	Value			Unit	Remark
	Min.	Typ.	Max.		
T1	0.5	-	10	[ms]	
T2	0	-	50	[ms]	
T3	500	-	-	[ms]	
T4	100	-	-	[ms]	
T5	0	-	50	[ms]	Note 3-5
T6	0	-	200	[ms]	Note 3-6
T7	1000	-	-	[ms]	

Note 3-5 : Recommend setting T5 = 0ms to avoid electronic noise when VDD is off.

Note 3-6: Voltage of VDD must decay smoothly after power-off. (Customer system decide this value)



Product Specification

AU OPTRONICS CORPORATION

7. Reliability Test Criteria

Items	Required Condition	Note
Temperature Humidity Bias (THB)	Ta= 50°C, 80%RH, 300hours	
High Temperature Operation (HTO)	Ta= 50°C, 300hours	
Low Temperature Operation (LTO)	Ta= 0°C, 300hours	
High Temperature Storage (HTS)	Ta= 60°C, 300hours	
Low Temperature Storage (LTS)	Ta= -20°C, 300hours	
Vibration Test (Non-operation)	Acceleration: 1.5 Grms Wave: Random Frequency: 10 - 200 Hz Sweep: 30 Minutes each Axis (X, Y, Z)	
Shock Test (Non-operation)	Acceleration: 50 G Wave: Half-sine Active Time: 20 ms Direction: ±X, ±Y, ±Z (one time for each Axis)	
Drop Test	Height: 45.7cm, package test	
Thermal Shock Test (TST)	-20 °C /30min, 60/ °C 30min, 100 cycles	1
On/Off Test	On/10sec, Off/10sec, 30,000 cycles	
ESD (Electrostatic Discharge)	Contact Discharge: ± 8KV, 150pF(330Ω) 1sec, 9 points, 25 times/ point.	2
	Air Discharge: ± 15KV, 150pF(330Ω) 1sec 9 points, 25 times/ point.	
Altitude Test	Operation:10,000 ft Non-Operation:30,000 ft	

Note 1: The TFT-LCD module will not sustain damage after being subjected to 100 cycles of rapid temperature change. A cycle of rapid temperature change consists of varying the temperature from -20°C to 50°C, and back again. Power is not applied during the test. After temperature cycling, the unit is placed in normal room ambient for at least 4 hours before power on.

Note 2: According to EN61000-4-2 , ESD class B: Some performance degradation allowed. No data lost. Self-recoverable. No hardware failures.

Note 3:

- Water condensation is not allowed for each test items.
- Each test is done by new TFT-LCD module. Don't use the same TFT-LCD module repeatedly for reliability test.
- The reliability test is performed only to examine the TFT-LCD module capability.
- To inspect TFT-LCD module after reliability test, please store it at room temperature and room humidity for 24 hours at least in advance.
- No function failure occurs.




Product Specification

AU OPTRONICS CORPORATION

8. Mechanical Characteristics

8.1 LCM Outline Dimension






- NOTE:
1. THE DIMENSION EXCLUDES DEFORMATION
 2. TOLERANCE WITHOUT NOTICED TO BE ±0.2MM
 3. DIMENSION REFERENCE POINT IS CENTER POINT WITHIN SHOT-PI, AND JUST RESCREW 5 TIMES
 4. USER HOLE SCREW PENETRATION IS 4.2MM MAX

AUO-General



Product Specification

AU OPTRONICS CORPORATION




AUO-General


9. Label and Packaging

9.1 Shipping Label (on the rear side of TFT-LCD display)




Note 1: For Pb Free products, AUO will add  for identification.

Note 2: For RoHS compatible products, AUO will add  for identification.

Note 3: For China RoHS compatible products, AUO will add  for identification.

Note 4: The Green Mark will be presented only when the green documents have been ready by AUO Internal Green Team.

9.2 Carton Package



Max capacity : 9 PCS TFT-LCD module per carton

Max weight : about 23 kg per carton

Outside dimension of carton : 566mm(L)* 395mm(W)*466mm(H)

Pallet size : 1150 mm * 840 mm * 138mm

Box stacked

Module by air_Max : (2 *2) *3 layers , one pallet put 12 boxes , total 108pcs module

Module by sea_Max : (2 *2) *3 layers + (2 *2) *1 layer , two pallet put 16 boxes , total 144pcs module

Module by sea_HQ_Max : (2 *2) *3 layers + (2 *1) *1 layer , two pallet put 16 boxes , total 144pcs module



10 Safety

10.1 Sharp Edge Requirements

There will be no sharp edges or comers on the display assembly that could cause injury.

10.2 Materials

10.2.1 Toxicity

There will be no carcinogenic materials used anywhere in the display module. If toxic materials are used, they will be reviewed and approved by the responsible AUO toxicologist.

10.2.2 Flammability

All components including electrical components that do not meet the flammability grade UL94-V1 in the module will complete the flammability rating exception approval process.

The printed circuit board will be made from material rated 94-V1 or better. The actual UL flammability rating will be printed on the printed circuit board.

10.3 Capacitors

If any polarized capacitors are used in the display assembly, provisions will be made to keep them from being inserted backwards.

10.4 National Test Lab Requirement

The display module will satisfy all requirements for compliance to:

UL 60950-1 second edition

U.S.A. Information Technology Equipment