



**SPECIFICATION
FOR
Flexible AMOLED Module**

MODULE No:	KD080WQOIN035
CUSTOMER:	

STARTEK	INITIAL	DATE
PREPARED BY		
CHECKED BY		
APPROVED BY		

CUSTOMER	INITIAL	DATE
APPROVED BY		



Revision History

[illegible]

Part. No	KD080WQOIN035	REV	V1.2	Page 2 of 42
----------	---------------	-----	------	--------------

Contents

1. Block Diagram	5
2. Outline dimension	6
3. Input terminal Pin Assignment	7
4. AMOLED Optical Characteristics	9
4.1 Optical specification	9
5. AMOLD Electrical Characteristics	16
5.1 Absolute Maximum Rating (Ta=25 VSS=0V)	16
5.2 DC Electrical Characteristics	16
6. AC Characteristic	17
6.1 MIPI Interface Characteristics	17
6.2 Display RESET Timing Characteristics	18
6.3 Timing for MIPI	19
7. Touch Specification	22
7.1 Electrical Characteristics	22
7.1.1 Absolute Maximum Rating	22
7.1.2 DC Electrical Characteristics (Ta=25°C)	22
8. Quality Level	23
8.1 AMOLED Module of Characteristic Inspection	23
8.2 Sampling Procedures for Each Item Acceptance Table	29
8.3 Telecommunications Inspection Item	29
8.4 Appearance Inspection Item	32
8.5 Inspection picture library	39
9. Reliability Test Result	40
10. Cautions and Handling Precautions	41
10.1 Handling Precautions:	41
10.2 Storage Precautions	41
10.3 Transportation Precautions:	41
11. Packing	42

* Description

This is a color active matrix Flexible AMOLED module using Low Temperature Poly-silicon Thin Film Transistors as active switching devices. This module has a 8.01 inch diagonally measured active area with 2480 horizontal by 1860 vertical pixel arrays. Each pixel is divided into RED and GREEN dots, or BLUE and GREEN dots, and two pixels share RED or BLUE dots which are arranged in vertical stripe and this module can display 16.7M colors.

* Features

General Information Items	Specification	Unit	Note
	Main Panel		
Display area(AA)	162.688(H)*122.016(V) (8.01 inch)	mm	
Driver element	active matrix	-	
Display colors	16.7M	colors	
Number of pixels	2480(RGB)*1860	dots	
Pixel pitch	0.065(H)*0.065(V)	mm	
Viewing angle	ALL	o'clock	
Driving Frequency	40Hz	-	No display is displayed when the value exceeds 40hz
Controller IC	RM69380	-	
Touch Controller IC	FT3881	-	
Touch Type	Oncell		
LCM Interface	MIPI	-	
Display mode	Flexible AMOLED	-	
Operating temperature	-40~+80	℃	
Storage temperature	-40~+85	℃	
Degree of curvature	R=3.5mm		


Notes:

1. The screen driver IC cannot be bent.
- 2.Refresh rate: 40Hz. Timing reference specification: Page 19.

* Mechanical Information

Item		Min.	Typ.	Max.	Unit	Note
Module size	Horizontal(H)		165.688		mm	-
	Vertical(V)		137.916		mm	-
	Depth(D)		0.341		mm	-
Weight			10		g	-

1. Block Diagram





Top View

165.688±0.2 (Panel Outline)
162.688 (Panel AA)
177.564±0.5
137.916±0.2 (Panel Outline)
122.016 (Panel AA)
137.916±0.2 (Panel Outline)
177.564±0.5
165.688±0.2 (Panel Outline)
162.688 (Panel AA)
177.564±0.5
137.916±0.2 (Panel Outline)
122.016 (Panel AA)
137.916±0.2 (Panel Outline)
177.564±0.5

8.01"
2480*1860
ALL

1.5
1.4
19.648
39.648±0.5
8.3
32.388
47.794±0.5
11.4
70.1±0.3
16.1±0.4 (BP)
16.1±0.4 (BP)
16.1±0.4 (BP)

Side View

0.34±0.2 (ALL)
0.104 (POL)
0.04 (Panel)
0.09 (BP)
0.059 (BP PF)
0.7±0.2 FPC+tape
0.33 FPC+Steel Stiffener

Back View

Pull Tab on POL PF
Steel Stiffener (T=0.1mm, Connected GND)
Connector type: BM035-140-C08

Pin	Symbol	Pin	Symbol
1	ELVSS	21	SMI06
2	TP-S0A	22	MPI1-D0N
3	ELVSS	23	TE
4	TP-D0N	24	GND
5	MPI-PWR	25	RST
6	TP-SCL	26	MPI1-CLRP
7	ELVDD	27	NC
8	TP-VDD	28	MPI1-CLDN
9	ELVDD	29	GND
10	TP-IOVCC	30	NC
11	AVDD	31	NC
12	TP-RST(NC)	32	NC
13	VDD1	33	NC
14	GND	34	MPI1-D0N
15	VCL	35	NC
16	MPI1-D0P	36	MPI1-D0P
17	NC	37	NC
18	MPI1-D0N	38	MPI1-D0N
19	AVDD1EN	39	NC
20	MPI1-D0P	40	GND

NOTES:

- DISPLAY TYPE: 8.01", OLED
- DISPLAY MODE: NORMALLY BLACK/IPS AMOLED Interface: MIPI
- VIEWING DIRECTION: ALL
- AMOLED DRIVER IC: RM69380 (COG), FT3881
- CIP Interface: I2C, CIP DRIVER IC: FT3881
- Operating Voltage: V0:2.65~4.8V VDDIO:1.65~1.95V ELVDD:4.6~5.0V, ELVSS:-5.4~-1.4V, AVDD:6~8V
- Operating Temp: -40°C TO 80°C
- Storage Temp: -40°C TO 85°C
- RoHS COMPLIANT.
- *** critical dimension() reference dimension.

SHENZHEN STARTEK ELECTRONICS CO., LTD

深圳市柯达科电子科技有限公司

DRAWING NAME: KD080WQ01N0315
PARTS NO: 97080029A
TOLERANCE UNLESS SPECIFIED: X.X±0.3 X.XX±0.2
Drawn: Charles
Checked: Charles
Approve: Charles
Scale: 1:1
Page: 1/1

深圳市柯达电子科技有限公司 SHENZHEN STARTEK ELECTRONICS CO., LTD		DRAWING NAME K080WQ01N035		PARTS NO. 97080029A	
TOLERANCE UNLESS OTHERWISE SPECIFIED	X.X4/0.3	Drawn	charles		Unit
	X.XX/0.2	Checked			mm
Scale 1:1		Approve			Page 1/1

NOTES:

1. DISPLAY TYPE: 8.01", OLED
2. DISPLAY MODE: NORMALLY BLACK/IPS AMOLED Interface: MIPI
3. VIEWING DIRECTION: ALL
4. AMOLED DRIVER IC: RM69380 (COG),
5. CTP Interface: I2C, CTP DRIVER IC: FT3881
6. Operating Voltage: VCI2.85~4.8V VDDIC1.85~1.35V ELVDD4.6~5.0V, ELVSS~5.4~1.4V, AVDD6~8V
7. OPERATING TEMP: -40°C TO 80°C
8. STORAGE TEMP: -40°C TO 85°C
9. RaHS COMPLIANT.
9. * * * critical dimension{ } reference dimension.

Part. No	KD080WQOIN035	REV	V1.2	Page 6 of 42
----------	---------------	-----	------	--------------

3. Input terminal Pin Assignment

FPC connector: BM035-I40-C08

NO.	SYMBOL	DISCRIPTION	I/O
1	ELVSS	AMOLED EL Negative power	P
2	TSP_SDA	Serial Data Signal for Touch Panel I2C I/F	I/O
3	ELVSS	AMOLED EL Negative power	P
4	TSP_INT	Interrupt Signal for Touch Panel	I/O
5	MTP_PWR	NC	P
6	TSP_SCL	Serial Clock Signal for Touch Panel I2C I/F	I/O
7	ELVDD	AMOLED EL Positive power	P
8	TSP_VDD	Analog Power for Touch Panel	P
9	ELVDD	AMOLED EL Positive power	P
10	TP_IOVCC	Analog Power for Touch Panel	
11	AVDD	AMOLED charge pumping power for DDIC	P
12	TP_RST	Reset Pin for Touch Panel	I/O
13	VDDI	AMOLED logic power for DDIC	P
14	GND	Ground	P
15	VCI	AMOLED logic power for DDIC	P
16	D2_P	MIPI Data Line	I/O
17	NC	NC	
18	D2_N	MIPI Data Line	I/O
19	AVDD_EN	AVDD enable	I/O
20	D1_P	MIPI Data Line	I/O
21	SWIRE	Control the PMIC	I/O
22	D1_N	MIPI Data Line	I/O
23	TE	Tear Effect	I/O
24	GND	Ground	P
25	REST	Drive IC reset	I/O



26	CLKP	MIPI CLK Line	I/O
27	NC	NC	
28	CLKN	MIPI CLK Line	I/O
29	GND	Ground	P
30	GND	Ground	P
31	NC	NC	
32	D0P	MIPI Data Line	I/O
33	NC	NC	
34	D0N	MIPI Data Line	I/O
35	NC	NC	
36	D3P	MIPI Data Line	I/O
37	NC		
38	D3N	MIPI Data Line	I/O
39	NC	NC	
40	GND	Ground	P

4. AMOLED Optical Characteristics

4.1 Optical specification


Item		Symbol	Condition	Min.	Typ.	Max.	Unit.	Note
Contrast Ratio		CR	Θ=0 Normal	400,000	--	--		(1)(3)
LCM Luminance		LV	White Mode	500	600		cd/m2	(1)(7)
Color gamut		S(%)	vs. NTSC	--	99	--	%	(5)
Color Filter Chromaticity	White	W _X		-0.04	0.300	+0.04		(1)(4)
		W _Y			0.315			
	Red	R _X			0.683			
		R _Y			0.317			
	Green	G _X			0.255			
		G _Y			0.713			
	Blue	B _X			0.134			
		B _Y			0.056			
Uniformity		U		80	/	/	%	(1)(6)
OLED Life Time				--	30000	--	Hrs	
Option View		ALL						

Test Conditions:


- the ambient temperature is 25℃.
- The test systems refer to Note1 and Note2.

Note 1: Definition of optical measurement system.

The optical characteristics should be measured in dark room. The optical properties are measured at the center point of the AMOLED screen. All input terminals AMOLED panel must be ground when measuring the center area of the panel.




Optical Characteristic Measurement Equipment and Method



Measuring point for surface luminance

Note 2: Definition of viewing angle range and measurement system.



Definition of viewing angle

Note 3: Definition of contrast ratio


$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when AMOLED is on the "white" state}}{\text{Luminance measured when AMOLED is on the "Black" state}}$$

"White state ": A state where the AMOLED should be driven by V_{white} .

"Black state": A state where the AMOLED should be driven by V_{black} .


Note 4: Definition of response time

The response time is defined as the AMOLED optical switching time interval between "White" state and "Black" state. Rise time (T_{ON}) is the time between photo detector output intensity changing from 90% to 10%. And fall time (T_{OFF}) is the time between photo detector output intensity changing from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of AMOLED.




Note 6: Definition of luminance uniformity

Active area is divided into 9 measuring areas. Every measuring point is placed at the center of each measuring area.

Luminance Uniformity(U) = Lmin/ Lmax

L-----Active area length W----- Active area width



Definition of uniformity

Lmax: The measured maximum luminance of all measurement position.

Lmin: The measured minimum luminance of all measurement position.

Note 7: Definition of luminance:

Measure the luminance of white state at center point.

Note 8: Cross Talk

There should be no visible cross-talk in normal direction of the display when the two "Cross-talk Test Patterns " below are loaded.

Measurement equipment: CS2000 or similar equipments

The point should be marked is, the background of Cross-talk Test Pattern-"gray " are defined as middle gray scale . For example, RGB 24bit "gray" defined as below:

R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0


Test pattern follow below picture, the background is middle gray and with two black rectangle parts, each one is 1/9 of the AA size.

Calculate the crosstalk(V) and crosstalk(H) with the test formula below:

$$Crosstalk(V)=\max\left(\left|\frac{L_{V1}-L_{V2}}{L_{V2}}\right|\times100,\left|\frac{L_{V3}-L_{V4}}{L_{V4}}\right|\times100\right)$$

$$Crosstalk(H)=\max\left(\left|\frac{L_{H1}-L_{H2}}{L_{H2}}\right|\times100,\left|\frac{L_{H3}-L_{H4}}{L_{H4}}\right|\times100\right)$$

Then use the max value between Crosstalk(V) and Crosstalk(H) as the final crosstalk.



Note 9: Image stacking

Test conditions:

Test instruments: Fast imaging photometer




Figure 7.9-1 gray scale 48 picture figure 7.9-2 black and white pattern figure 7.9-3 calculation area

The test procedure for short time image sticking is as follows:

- 1) Display the 48 gray scale pattern in full screen, measure the brightness, and calculate the X value.
- 2) Switch to the black and white pattern and keep it for 10s.
- 3) Switch to the 48 gray scale pattern. Use the CCD to measure the luminance of the red frame. The exposure time of the CCD is 0.3s. The test is performed 60 times at an interval of 1s. The captured luminance values are as follows:
- 4) Calculate the X value.

$$IS(ST) = \left| \frac{I(t)_A - I(t)_B}{I(t)_A + I(t)_B} - \frac{I(0)_A - I(0)_B}{I(0)_A + I(0)_B} \right|$$

$$JND=IS(ST)/0.004$$

The test procedure for medium-term image sticking is as follows:

- 1) Display the 127 gray scale pattern in full screen, measure the brightness, and calculate the X value.
- 2) Switch to the black and white pattern and keep it for 10min.
- 3) Switch to the 127 gray scale pattern. Use the CCD to measure the luminance of the red frame. The exposure time of the CCD is 0.3s. The test is performed 3600 times at an interval of 1s. The captured luminance values are as follows:
- 4) Calculate the X value.




$$IS(ST) = \left| \frac{I(t)_A - I(t)_B}{I(t)_A + I(t)_B} - \frac{I(0)_A - I(0)_B}{I(0)_A + I(0)_B} \right|$$

$$JND = IS(ST) / 0.004$$

Note 10: Flicker

- 1) Measurement equipment: CA-310 or similar equipment.
- 2) Measuring temperature: Ta=25℃.
- 3) JEITA method can be used to supply software for CA310.
- 4) Test pattern: W255&W128&W32.
- 5) Frame Frequency Requirement: AOD\60Hz\90Hz\120Hz, etc. (The flicker at all frequency mode need to be tested)
- 6) Calculation formula Flicker = $10 \times \log (P_x/P_0)$ [dB]

Data processed by FFT analyzer



5. AMOLD Electrical Characteristics

5.1 Absolute Maximum Rating (Ta=25 VSS=0V)

Characteristics	Symbol	Min.	Max.	Unit
Analog Power supply	VCI	2.65	4.8	V
Logic Power supply	VDDIO	1.65	1.98	V
Logic Power supply	DVDD	1.1	1.25	
Analog Power supply	AVDD	6.0	8.0	V
Positive Power Input	ELVDD	4.6	5.0	V
Negative Power Input	ELVSS	-5.4	-1.4	V
Operating temperature	T _{OP}	-40	+80	°C
Storage temperature	T _{ST}	-40	+85	°C


NOTE: If the absolute maximum rating of even is one of the above parameters is exceeded even momentarily, the quality of the product may be degraded. Absolute maximum ratings, therefore, specify the values exceeding which the product may be physically damaged. Be sure to use the product within the range of the absolute maximum ratings.

5.2 DC Electrical Characteristics


Characteristics	Symbol	Min.	Typ.	Max.	Unit	Note
Logic Power Supply	VDDIO	1.65	1.8	1.98	V	--
Analog Power Supply	VCI	2.6	3.3	3.6	V	--
Analog Power Supply	AVDD	4.5	7.6	8	V	--
Positive Output Voltage	ELVDD	--	4.6	--	V	--
Negative Output Voltage	ELVSS	--	-2.4	--	V	--
Level input voltage	V _{IH}	0.8*VDDIO	--	VDDIO	V	--
	V _{IL}	0	--	0.2*VDDIO	V	--
Level output voltage	V _{OH}	0.8*VDDIO	--	VDDIO	V	--
	V _{OL}	0	--	0.2*VDDIO	V	--

6. AC Characteristic


6.1 MIPI Interface Characteristics



HS clock transmission (D-PHY)



HS Data Transmission in Burst (C-PHY)




6.2 Display RESET Timing Characteristics

Reset input timing:

If Reset starts in Sleep-Out mode the display driver will enter blanking sequence with maximum time 120 msec. On the other hand, the display driver will remain in blanking state if Reset occurs in Sleep-In mode and then return to IC's default state soon after HW reset. "Spike Rejection" also applies during a valid reset pulse as shown below.

During reset complete time (t_{REST}), data in MTP will be re-loaded and latched to internal registers. This data re-load is done every time when there is an HW reset and completes within 10ms after the rising edge of RESX. Therefore, it is necessary to wait at least 10ms after releasing RESX before sending commands. Also, the rising edge of RESX to Sleep-Out command should be longer than 120msec.



Reset timing @VDDI=1.65V to 1.98V, VSSA=DVSS=VSSI=0V, Ta=-40°C to 85°C

Symbol	Parameter	MIN	TYP	MAX	Note	Unit
t_{RESW}	Reset low pulse width	15	-	-	1. Shorter than 5us, Reset rejected 2. Longer than 15us, IC reset 3. Between 5us and 15us, It depends on voltage and temperature condition.	μs
t_{REST}	Reset complete time	-	-	10	When reset applied at sleep-in mode	ms
		-	-	120	When reset applied at sleep-out mode	ms



6.3 Timing for MIPI

Parameter	Symbol	Min.	Typ.	Max.	Unit
DCLK frequency	FCLK	--	(189)	--	MHz
Horizontal display area	HDISP	--	2480	--	Clock
Horizontal Sync. Width	hpw	-	-	--	Clock
Horizontal Sync. Back Porch	hbp	--	10	-	Clock
Horizontal Sync. Front Porch	hfp	--	10	--	Clock
Vertical display area	VDISP	--	1860	--	Line
Vertical Sync. Width	vs	--	--	--	Line
Vertical Sync. Back Porch	vbp	--	8	--	Line
Vertical Sync. Front Porch	vfp	--	20	--	Line
Frame-Rate		--	40	--	Hz

Note: 1. Typical value are related to the setting frame rate is 40Hz.

6.4 Power Structure and On/Off Sequence

Power Mode Summary

◆ BSTM Control


BSTM	Power Mode	Note
0	4 Power mode : VDDI, VCI, AVDD(from Power IC), DVDD	External component: Power IC + flying capacitors
1	3 Power mode : VDDI, VCI, AVDD(from Power IC)	

Note :

1. BSTM control whether internal DVDD regulator is turned on.(BSTM=1, internal DVDD on ; BSTM=0, internal DVDD off)
2. When the system uses both internal and external DVDD regulator, please set BSTM=1 and external DVDD follow power on/off sequence.

Power On/Off Sequence

❖ Power On Sequence




◆ Timing Specification of Power On Sequence

Symbol	Value			Unit	Remark
	Min.	Typ.	Max.		
TON1	0	-	-	ms	VDDI-to-DVDD power ready time(for external DVDD power)
TON2	0	-	-	ms	DVDD-to-VCI power ready time(for external DVDD power)
TON3	0	-	-	ms	VDDI-to-VCI power ready time
T1	10	-	-	ms	Effective hardware reset period
T2	10	-	-	ms	OTP reload time
T3	0	-	-	ms	Initial code input finish to SLPOUT command input
T4	-	96	-	ms	Normal power-up sequence
T5	2	-	-	VS	Display-On Blanking region

Notes: VS means the time period of a complete display frame and are approximately 16ms if internal display timing is used.

❖ Power Off Sequence



Symbol	Value			Unit	Remark
	Min.	Typ.	Max.		
T6	2	-	-	VS	Display-Off blanking region
T7	1	-	-	VS	Power-Off blanking region
T8	1	-	-	ms	Effective hardware reset period
TOFF1	2	-	-	ms	Power off period (for external DVDD power)
TOFF2	0	-	-	ms	Power off period (for external DVDD power)
TOFF3	2	-	-	ms	Power off period

Notes: VS means the time period of a complete display frame and are approximately 16ms if internal display timing is used.

7. Touch Specification

7.1 Electrical Characteristics

7.1.1 Absolute Maximum Rating

Item	Symbol	Min.	Max.	Unit	Note
TP power supply Input	TP_VDD	2.8	3.6	V	
TP power supply for logic circuits	TP_IOVCC	1.65	1.98	V	
Operating temperature	T _{OP}	-40	+80	°C	
Storage temperature	T _{ST}	-40	+85	°C	

7.1.2 DC Electrical Characteristics (Ta=25°C)

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Touch logic power	TP_VDD	2.8	3.0	3.6	V	
Touch analog power	TP_IOVCC	1.65	1.8	1.98	V	

8. Quality Level

8.1 AMOLED Module of Characteristic Inspection

The environmental condition and visual inspection shall be conducted as below:

8.1.1 Inspection conditions

Test conditions: OLED is not light, cold white fluorescent lamp, illumination 1000 ± 200 lux; OLED lighting source shall not be higher than 200lux, with black background around.

8.1.2 Inspection distance: the standard observation distance of all surfaces of the tested object is $30\text{cm} \pm 5\text{cm}$.


8.1.3 Inspection angle: the angle between the product and the horizontal plane is 45° , and the eyes are perpendicular to the inspection plane. During inspection, the product needs to rotate 45° up, down, left and right. The observation line of sight needs to be within the half section of the cone. The observation angle is 45° with the vertical axis of the product apex. The central axis of the cone must be standard and perpendicular to the product surface and pass through the fluorescent lamp; For non-conventional display defects (including but not limited to local bright lines or local floodlights), the observation angle is 75 degrees from the normal of the product surface; Full visual angle of appearance.

8.1.4 Inspection time: the inspection time without lighting is at least 10-12 seconds; The time of OLED lighting inspection for each picture is 1~3 seconds. If the defect is still not visible within the specified time, the inspection piece is deemed to be qualified.


8.1.5 Test temperature: room temperature $15-35^\circ\text{C}$, ambient humidity: 20-75% RH.

8.1.6 Inspection tools:

ND Filter: The ND Filter is placed at a distance of 2-3 cm above the defect for 2-3s to judge whether the defect is visible. As Figure below: (ND Filter is used to test mura isochromatic and light unevenness)



Point gauge (point gauge in the figure below is recommended), determination method: as shown in the figure, the point gauge film can cover is pass, and the point gauge film can not cover is Fail。 For example, a maximum of 0.2mm same-color spot defect is allowed on the Class A surface, and the pass that can be covered by 0.2mm on the film, The one that can be covered is Fail.



Digital caliper: resolution 0.01mm.


Projector: anime microscope, 3D projector.




Judgment description





The measurement accuracy shall refer to the specification definition. When the measurement equipment accuracy is higher than the specification definition, the measured value needs to be rounded to the precision defined by the specification. For example, the size of edge collapse is 0.20mm, and the thousandth is the reference position, which is rounded to 0.200mm~0.204mm is OK, $\geq 0.205\text{mm}$, it is judged as NG.



In addition to the tools used above, if additional inspection tools are needed to assist the judgment, they can only be carried out after the coordination of both parties.

Bad code and definition

Code and name		legend	explain
N	Number	-	Visually calculate the number; The statistics of the total number of defects does not include the completely "omitted" part. For the column defined as "omitted" and "omitted", it is not counted as the number of defects if it meets the requirements, otherwise it is calculated as an independent defect.
L	Length (mm)		Dot line distinguishing rule: L is the long side, W is the short side A. When $L > 3W$, handle as per line, otherwise handle as per point;
W	Width (mm)		B. When it is judged as line defect, S-shaped or C-shaped line appears, and the enclosed amount is less than 3/4 circle, it shall be treated as line defect; otherwise, it shall be treated as point defect, and the inner tangent circle shall simulate the size of point.
S	Area (mm ²)	-	Surface gauge
D	Diameter (mm) $D=(L+W)/2$	-	Point diameter calculation: calculated by half of the sum of the long side and the short side, that is,

			$D = (L+W)/2$, where D represents the diameter of the point, L is the long side, and W is the short side;
H	Depth (mm)	-	Digital micrometer
DS	Distance (mm)		Distance between two points or between two lines
Schematic diagram of screen area			AA area: display area; GA area: GIP circuit area; FA area: Frit area; OA area: outside FA area
Leader area			Screen GIP circuit area, screen data circuit area
PAD Bangding District			COG/FOG Bonding alignment mark and Bonding Pad on LTPS substrate
PAD Non-state area			Screen test pad, cutting area and lead-free area on LTPS substrate
CT crimping area			Pin end screen test pad

Highlights		A single sub-pixel (or red, or green, or blue) of one pixel is called a point; The definition of bright spot is that in the environment of 200 ± 50 Lux, the pixels or dots seen by employees with naked eyes are always bright, and the bright spot is checked under the black screen
Scotoma		A single sub-pixel (or red, or green, or blue) of one pixel is called a point; A dark point is defined as a point that is not bright in a single sub-pixel seen with naked eyes in a 100% white picture under the environment of 200 ± 50 Lux.
Dark spot - two connection		Two adjacent sub-pixels under the magnifying glass are not bright at the same time (horizontal, vertical and oblique)
Dark Spot - Three Links		The adjacent R, G and B sub-pixels under the magnifying glass are not bright at the same time (horizontal, vertical and oblique)
CG monomer area division		AA: Front visible area, black ink internal area; A: Black ink area; B: Cover plate edge; The front defect that runs through the AA area and the A area shall be judged according to the specification of the strictest area, and the back defect shall be judged according to whether the AA area is visible.
Foreign matter highlights	-	Due to the foreign matter in the polarizer, the phenomenon that appears as a bright spot is called a foreign matter bright spot

point defect		There are bright spots and black spots in local positions, including but not limited to the internal dirt of the screen itself, pinholes, serrations, concave-convex spots, color spots, tiny bubbles, white spots, stains on the fitting of the polarizer, poor polarizer itself and other spot-like defects. Point defects are judged by diameter.
Linear defect		Linear impurities in the screen, including filaments, fibers, polarizer fitting impurities in the screen, and scratches on the surface of polarizer, etc. Linear defects are judged by length and width. Sensible scratch: also known as hard scratch, is a deep scratch on the surface, which is felt by hand. Senseless scratch: also known as fine scratch, no deep scratch on the surface, no feeling when touching.
Serrated defect		W: Distance from sawtooth crest to trough
Edge collapse/angle collapse		In the process of screen production, especially in the process of molding and cutting, the small glass missing at the glass edge is caused. X direction: parallel to FOG Pad or glass edge; Y direction: perpendicular to FOG Pad or glass edge; Z direction: screen thickness direction; T : The thickness of single-layer glass;
Pitting	-	In the unit area of 10mm * 10mm, the defect point with $D \leq 0.1\text{mm}$, $DS \geq 2\text{mm}$, and the number $N \geq 5$. If the customer has other requirements, follow the customer's requirements.

Dirty	-	Including handprints, oil stains, fingerprints, stains, white fog and other undesirable phenomena. It is divided into erasable dirt and non-erasable dirt. Use a dust-free cloth dipped in alcohol, which can not be erased as non-erasable dirt. Wipable dirt is determined as follows: A. Dry dust-free cloth can be directly erased; B. Wipe with clean cloth dipped with anhydrous alcohol Press the alcohol-stained dust-free cloth on the dry dust-free cloth twice to absorb excess alcohol; Wipe back and forth with a dust-free cloth twice, and the dirt can be removed.
-------	---	--

8.2 Sampling Procedures for Each Item Acceptance Table

Critical Defect (CR): any defect that directly or indirectly affects human health and safety, or the function of the product is lost.

Major Defect (MA): directly or indirectly affect the product function, or make part of the product function lost, and other customers do not acceptable defects.

Minor Defect (MI): appearance defect that does not affect product function and can be accepted by customers.

Defect Type	Sampling Procedures	AQL
Critical Defect (CR)	Take the normal inspection solution of the sampling plan of GB/T2828.1-2012 Inspection level II	0.065
Major Defect (MA)	Take the normal inspection solution of the sampling plan of GB/T2828.1-2012 Inspection level II	0.65
Minor Defect (MI)	Take the normal inspection solution of the sampling plan of GB/T2828.1-2012 Inspection level II	1.0

8.3 Telecommunications Inspection Item

category	NO.	Inspection Items	Inspection specification	test mode	defect type
	1	Display exception	not allow	visual	CR

Poor function	2	No display	not allow	visual	CR
	3	The picture flickers	not allow	visual	MA
TP function	4	TP test NG	not allow	visual	MA
Dot	5	Bright dot	not allow	visual	MI
	6	Partial Bright dot	ND6% or reference limit sample	visual	MI
	7	Dark dot	1.D≤0.15mm, ignored; 2.0.15mm < D≤ 0.2mm, DS ≥ 10mm, N ≤ 10; 3.D > 0.2mm,not allowed;	Visual inspection, Flinka	MI
Line	8	Bright line	not allow	visual	MA
	9	Dark line	not allow	visual	MA
	10	Slightly bright line	not allow	visual	MA
Mura	11	horizontal mura	No control under W64/127 screen; The 4%ND Filter on the 255 screen determines that the invisible is OK and the visible is NG.	Visual ND Filter/limit sample	MI
	12	vertical mura	No control under W64/127 screen; The 4% ND Filter on the 255 screen determines that the invisible is OK and the visible is NG.	Visual ND Filter/limit sample	MI
	13	White spot	No control under W64/127 screen; The 4% ND Filter on the 255 screen determines that the invisible is OK and the visible is NG.	Visual ND Filter/limit sample	MI
	14	Black spot	No control under W64/127 screen; The 4% ND Filter on the 255 screen determines that the invisible is OK and the visible is NG.	Visual ND Filter/limit sample	MI
	15	Color mura	4% ND Filter in W64/255 screen determines that the invisible is OK and the visible is NG	Visual ND Filter/limit sample	MI





	16	snowflake	No control under W64/127 screen; The 4% ND Filter on the 255 screen determines that the invisible is OK and the visible is NG.	Visual ND Filter/limit sample	MI
	17	Twill mura	No control under W64/127 screen; The 4% ND Filter on the 255 screen determines that the invisible is OK and the visible is NG.	Visual ND Filter/limit sample	MI
	18	Newtonian ring	No control under W64/127 screen; The 4% ND Filter on the 255 screen determines that the invisible is OK and the visible is NG.	Visual ND Filter/limit sample	MI
	19	Uneven transition	Reference homogeneity standard to assist in judgment; The 4% ND Filter in the W64/255 screen determines that the invisible product is OK and the visible product is NG.	Visual ND Filter/limit sample	MI
	1、 Mura all specify the screen judgment. For example, if the ELA mura judgment standard is 255, the ELA mura will only be judged on the W255 screen. 2、 Other types of mura have a low adverse effect rate and low incidence. According to the 4% ND Filter in the W64/255 screen, the invisible products are OK and the visible ones are NG.				
Dot/line of foreign material	20	Dot/line defects (foreign material, black white dot, scratch, bubble, etc.)	Same point/line specifications	Visual inspection/Fli nka	MI



8.4 Appearance Inspection Item

NO.	Inspection items	Surface Area	Inspection specification	test mode	defect type
1	Broken glass	AA/OA	not allow	visual	MA
2	crack	AA/OA	not allow	visual	MA
3	Edge collapse/corner	AA/OA	1. $Y \leq 0.15\text{mm}$, X and N are ignored; 2. $0.15 < Y \leq 0.4\text{mm}$, $X \leq 2\text{mm}$, N is ignored; 3. $Y > 0.4\text{mm}$, not allowed; 4. $Z \leq t$, without damage to Frit body;	Visual inspection, Flinka	MI



					
4	flange	AA/OA	1. $Y \leq 0.2\text{mm}$, X is uncontrolled; 2. $Y > 0.2\text{mm}$, not allowed; 	Visual inspection, Flinka	MI
5	Glass warp	Whole area	 The product is placed horizontally on the front and back, and the lifting height at one end (plug gauge) $\leq 0.6\text{mm}$	Visual inspection, Flinka	MI
6	Pin dirty	Bongding area	No control	visual	MI
7	Pin scratch	Bongding area	Scratches and whitening are found by visual inspection, and need to be rechecked with a microscope. The broken lead is not allowed, and the overlap is not allowed Note: CT pad area and pin non-bonding area are not controlled	visual	MI
8	PF film bump	LTPS	Touch is not allowed	visual	MI
9	PF film pinholes/pits	LTPS	No control	visual	MI
10	PF film scratch	LTPS	1. No scratch, no control; Scrape through, $L < 10\text{mm}$; 2. The film shall be scraped through the exposed glass surface, referring to the lack of glue of PF film;	Visual inspection, Flinka	MI
11	PF film lacks glue	LTPS	$50 > 5\text{mm}$, $W > 5\text{mm}$ not allowed	Visual inspection, Flinka	MI
12	PF membrane is dirty	LTPS	Wipable dirt needs to be wiped, and non-wipe dirt refers to the color difference of PF film;	visual	MI
13	PF film overflow	LTPS	1. Edge overflow $W < 0.2\text{mm}$, acceptable; 2. $W > 0.2\text{mm}$, not allowed;	Visual inspection, Flinka	MI



14	Color difference/stain (no convex touch)	LTPS	No control			visual	MI	
15	PF film gluing offset	LTPS	1. Step area is not allowed; 2. Except for the step area, the rest shall be controlled by $0.5 \pm 0.2\text{mm}$;			Visual inspection, Flinka	MI	
16	Screen body is dirty	LTPS	1. The front can be wiped and the dirt can be wiped, and the polarizer of the dirt cover cannot be wiped; 2. The back is not controlled;			visual	MI	
17	point defect	AA	D (mm)	DS (mm)	Acceptable number	Visual inspection, Flinka	MI	
			$D \leq 0.15\text{mm}$	/	Ignore			
			$0.15\text{mm} < D \leq 0.2\text{mm}$	$DS \geq 10$	$N \leq 10$			
18	Linear defect/foreign matter linear/non-inductive scratch	AA	W (mm)	L (mm)	DS (mm)	Acceptable number	Visual inspection, Flinka	MI
			$W \leq 0.03$	$L \leq 5$	≥ 10	ignore		
			$0.03 < W \leq 0.05$	$L \leq 2$	≥ 10	ignore		
			$0.03 < W \leq 0.05$	$2 < L \leq 5$	≥ 10	$N \leq 4$		
			$W > 0.05$	-	/	Not allowed		
			-	$L > 5$	/	Not allowed		
19	Point/Line defects	Camera hole area/Blind hole area	D(mm)		Acceptable number		Visual inspection, Flinka	MI
			$D \leq 0.15$		ignore			
			$0.15 < D \leq 0.2$		ignore			
			$D > 0.2$					
20	Newton rings (Blind hole area)	Camera hole area/Blind hole area	Not control			Visual inspection	MI	
21	offset	Camera hole	The metal ring extends inward 0.1mm ,ignore			Visual inspection	MI	



		area/Blind hole area			
22	Blind hole color bias(same color)	Camera hole area/Blind hole area	Functional requirements such as transmittance and PV value are met, not control appearance	Visual inspection	MI
23	Protective film scratch	Whole area	No control under no hurt body	Visual inspection	MI
24	Protective film starved/overflow glue/burr	Whole area	No control under no hurt body	Visual inspection	MI
25	Dirt inside the protective film	Whole area	Not allowed	Visual inspection	MI
26	Easy to tear	Cover front	Function is invalid, damaged, leaked not allowed Wrinkles, bumps, dirt, punching bad, burr, overflow glue is not controlled	Visual inspection	MI
27	Polarizer edge overflow	AA	$W \leq 0.35\text{mm}$, Not control; $W > 0.35\text{mm}$, Not allowed.	Visual inspection, Flinka	MI
28	Polarizer concave convex point	AA	convex point: $D \leq 0.2\text{mm}$ or refer to limit sample concave point: $D \leq 3\text{mm}$, $DS \geq 10\text{mm}$, $N \leq 3$ or refer to limit sample	Visual inspection, Flinka	MI
29	Polarizer fold / indentation	AA	Does not affect the display as OK or refer to limit sample;	Visual inspection	MI
30	Polarizer chromatism	AA	No control	Visual inspection	MI
31	IC chip	IC	Not allowed	Visual inspection	MI
32	FPC body defect	FPC	1. The parts on the FPC must be consistent with the product BOM table, and there are incorrect, multiple, or missing parts, which are not allowed; Polarities such as capacitors and inductors should not be soldered backwards or crooked; 2. FPC scratches/scratches are based on the absence of exposed copper; 3. Creases/Indentations: Indentations in the circuit area should not cause the back of the	Visual inspection	MI



			covering film to turn white; Non line area indentation should not cause FPC damage 4. Except for the golden finger. FPC foreign object: a. Spot shape: $D \leq 0.5\text{mm}$, $N \leq 3$; b. Linear: length and width $\leq 0.3 * 5\text{mm}$;		
33	FPC gold finger defect	Golden Finger Region	1. Golden finger cracking: The length and width of the crack/damage at the top of the golden finger $\leq$ the line width; 2. Gold finger copper leakage: $W \leq 1/3$ line width, $L \leq$ line width, unlimited quantity 3. Gold finger gap $W1 \leq 1/3$ line width W , length $L1 \leq 1/2$ line width W , unlimited quantity, all of the above conditions are met and allowed; 4. Gold finger pressure/scratch should not expose copper, there should be no unevenness, and there should be no depth visible to the naked eye, which does not affect assembly and is acceptable; 5. Gold fingers should not have sharp creases or dead folds; 6. FPC gold fingers should not have oxidation, blackening, burns, or browning;	Visual inspection	MI
34	connector	connect or	There should be no tin or residual solder beads on the connector, and there should be no tin connection on the connector pins; PIN deformation shall be controlled within 0.05mm; Does not affect the lighting function; Visual inspection of pin breakage, pin detachment, and deformation of the outer frame is not allowed;	Visual inspection	MI
35	Insulating tape	Bonding area	There must be no obvious wrinkles or bubbles	Visual inspection	MI
		Component area	1. Scratches and glue splashes are uncontrollable; 2. Do not wipe dirt or dirt; 3. The offset of the insulation tape should not exceed the edge of the product, and other requirements should be determined based on the drawing; 4. Burr edges, no control over glue overflow;		










			5. Damaged, incomplete, or missing labels are not allowed;		
36	Composite tape	All	1. It is not allowed for the composite tape to leak out of the edge of the screen body; 2. Folding of composite tape, light leakage during assembly, or affecting assembly and thickness are not allowed; 3. Damaged composite tape is not allowed; 4. The size of the composite tape cutting defect does not meet the requirements of the drawing and cannot be controlled; 5. Composite tape should not be wiped with dirt or foreign objects, and foreign objects should follow the dotted line standard; 6. The burrs of the composite tape should not exceed the edge of the screen body, regardless of control; 8. Composite adhesive tape with no control over glue splashes or overflow; 9. Composite tape bubbles: $D \leq 5\text{mm}$, N not included; 10. Composite tape bumps: acute angle bumps $D \leq 0.3\text{mm}$, $N \leq 3$; Smooth concave convex points $D \leq 0.8\text{mm}$, $N \leq 3$; 11. Composite tape foreign object (foreign object between copper foil and blue film): $D \leq 0.3\text{mm}$, $N \leq 3$; 12. Edge sawtooth of composite tape: $0.5 * 3\text{mm}$, $N \leq 3$; 13. The color difference of the protective film in the composite tape is not controlled; 14. Copper foil indentation and dead bending in composite tape are not allowed, which does not affect assembly and thickness control; Or reference limit sample; 15. No control of foreign objects/dents in copper foil in composite tape;	Visual inspection	MI
37	OCA overflow	All	Not allowed within AA area; Externally visible: Control standard $\leq 0.15\text{mm}$	Visual inspection	MI



38	Sealing glue	Pin	1. Broken adhesive is not allowed, and the circuit cannot be exposed. 2. The thickness of the colloid shall not be higher than the POL surface. 3. Bubble diameter<1mm. 4. Other: According to the drawings and work instructions.	Visual inspection	MI
39	Conductive cloth	All	1. Conductive cloth dirt: $D \leq 5\text{mm}$, $N \leq 2$; 2. Conductive cloth bubbles: $D \leq 2\text{mm}$, $N \leq 2$; 3. Conductive cloth foreign object: $D \leq 1\text{mm}$, $N \leq 3$; 4. Folding of conductive fabric: $N \leq 2$;	Visual inspection	MI
40	Copper foil	All	Copper foil sticking is not allowed to leak out of the edge of the screen body; Abnormal color of copper foil refers to standard samples/sealed samples, and damage is not allowed. Soft scratches on the surface are not controlled.	Visual inspection	MI
41	QR code	QR code	It is not allowed to be unable to scan or difficult to scan (recognition can only be achieved after three consecutive scans), with a clear appearance, no blurring, missing printing, and other defects	Visual inspection	MI
42	Package	Other	Products should put into the anti-static trays, with non-overlapping, and the trays should be staggered placed. Different products cannot be mixed into the same inner package. The package should not have obvious deformation or breakage .The printing labels type and quantity are correct. The package should have QC signature. ROHS label is needed if the product is under ROHS control.	visual	-
43	Boundary dimension NG	Other	It is not allowed to exceed the dimensional tolerance required by the specifications and drawings	Calipers, measuring instruments	-



8.5 Inspection picture library

Serial number	picture	Picture name	Mainly judged as defective	remarks
1		W_GRAD(64) 64 gray scale	Point/line type, foreign matter point/line, mura type	/
2		W_GRAD(128) 128 gray scale	Point/line type, foreign matter point/line, mura type	/
3		WHITE white	Point/line type, foreign matter point/line, mura type	/
4		Black black	Bright spot, bright line, dark mura	/
5		RED red	Point type, line type, foreign matter point/line	/
6		GREEN green	Point type, line type, foreign matter point/line	/
7		BLUE blue	Point type, line type, foreign matter point/line	/

Note: The actual sequence and lock seconds of the screen can be adjusted according to the customer's requirements and the needs of the factory.

9. Reliability Test Result

Item	Condition	Inspection after test
High Temperature Operating	80℃,96H	IEC60068-2-2,GB2423.2
Low Temperature Operating	-40℃, 96HR	IEC60068-2-1 GB2423.1
High Temperature Storage	85℃, 96HR	IEC60068-2-2 GB2423.2
Low Temperature Storage	-40℃, 96HR	IEC60068-2-1 GB2423.1
High Temperature & High	+60℃, 90% RH ,96 hours.	IEC60068-2-78 GB/T2423.3
Thermal Shock (Non-operation)	-40℃,30 min ↔ 85℃,30 min, Change time:5min 20CYC.	Start with cold temperature, End with high temperature, IEC60068-2-14,GB2423.22

Note: Product reliability items in the form of GK are used as reference items. The test results shall refer to the results of the reliability test of Visionox standards.

10. Cautions and Handling Precautions

10.1 Handling Precautions:

- (1) The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from height..
- (2) Do not press down the screen or the adjoining areas too hard because the color tone may be shifted.
- (3) The polarizer covering the display surface of the AMOLED module is soft and easily scratched. Handle this polarizer carefully.
- (4) If the display surface is contaminated, blow on the surface and gently wipe it with a soft dry cloth. If it is still not completely clear, moisten the cloth with ethyl alcohol.
- (5) Solvents may damage the polarizer. Do not use water, ketone or aromatic solvents except ethyl alcohol.
Do not attempt to disassemble the AMOLED Module.
- (6) If the logic circuit power is off, do not apply the input signals.
- (7) To prevent destruction from static electricity, be careful to maintain an optimum working environment.
- (8) Be sure to make yourself in contact with the ground when handling with the AMOLED Modules.
- (9) Tools required for assembly, such as soldering irons, must be properly ground.
- (10) To reduce the generation of static electricity, do not conduct assembly or other work under dry conditions.
- (11) To protect the display surface, the AMOLED Module is coated with a film. Be careful when peeling off this protective film, because static electricity may generate.

10.2 Storage Precautions.

- (1) When storing the AMOLED modules, be sure that they are not directly exposed to the sunlight or the light of fluorescent lamps.
- (2) The AMOLED modules should be stored under the storage temperature range. If the AMOLED modules will be stored for a long time, the recommended condition is: Temperature: 0℃~40℃ Relatively humidity: ≤80%
- (3) The AMOLED modules should be stored in the room without acid, alkali or harmful gas.

10.3 Transportation Precautions:

- (1) The AMOLED modules should not be suffered from falling and violent shocking during transportation. Besides, excessive press, water, damp and sunshine, should be avoided.



11. Packing

----TBD-----