




# Ceramic Patch Antenna

## AGR7106-ES

### Datasheet V2.0



## Notice, Statement and Copyright

ALLYSTAR Technology offers this document as a service to its customers, to support application and engineering efforts that use the products designed by ALLYSTAR Technology. Products and specifications discussed herein are for reference purposes only. Performance characteristics listed in this document do not constitute a warranty or guarantee of product performance.

ALLYSTAR Technology assumes no liability or responsibility for any claims or damages arising out of the use of this document, or from the use of integrated circuits based on this document, including, but not limited to claims or damages based on infringement of patents, copyrights or other intellectual property rights.

This document contains proprietary technical information which is the property of ALLYSTAR Technology, copying of this document and giving it to others and using or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. ALLYSTAR Technology reserves the right to make changes in its products, specifications and other information at any time without notice.

For more recent documents, please visit [www.allystar.com](http://www.allystar.com).

Copyright © Allystar Technology (Shenzhen) Co., Ltd. 2018. All rights reserved.

## TABLE OF CONTENT

<b>TABLE OF CONTENT .....</b>	<b>3</b>
<b>1 PRODUCT OVERVIEW.....</b>	<b>5</b>
1.1 General description.....	5
1.2 Features.....	5
1.3 Product image .....	5
<b>2 SPECIFICATIONS .....</b>	<b>6</b>
2.1 Dimensions.....	6
2.2 Layout Dimensions.....	6
2.3 Antenna performance.....	6
2.4 Reliability.....	7
2.5 Antenna S Parameter Data.....	7
<b>3 TEST .....</b>	<b>8</b>
3.1 Test Conditions.....	8
3.2 Ground Plane Dimension .....	8
3.3 Test Jig .....	8
<b>4 ENVIRONMENTAL TEST .....</b>	<b>8</b>
<b>5 PACKAGE .....</b>	<b>10</b>
5.1 PACKING .....	10
5.2 Disposal information .....	11
<b>6 ORDERING CODES.....</b>	<b>11</b>
<b>7 REVISION HISTORY.....</b>	<b>11</b>

## List of tables

Table 1 Antenna performance.....	6
Table 2 Reliability .....	7
Table 3 ENVIRONMENTAL TEST.....	8
Table 4 Test.....	10
Table 5 PACKING.....	10
Table 6 ORDERING CODES.....	11

## List of figures

Figure 1 Product image .....	5
Figure 2 Dimensions.....	6
Figure 3 Layout Dimensions .....	6
Figure 4 S Parameter Data .....	7
Figure 5 Ground Plane .....	8
Figure 6 Test Jig .....	8
Figure 7 press test .....	10
Figure 8 PACKING .....	10

## 1 PRODUCT OVERVIEW

### 1.1 General description

The AGR7104 patch antenna are use Allystar's unique technology to customize for customer device, which support the GNSS L1 band and show the good performance of AR and RHCP on practical application, just like tracker, navigation device and autonomous vehicles.

Customizer service of antenna design and measurement that can follow your request and contact the Allystar window.

### 1.2 Features

- Support GPS L1
- Great AR
- One pin feed in
- RoHS Compliant

### 1.3 Product image



Figure 1 Product image

## 2 SPECIFICATIONS

### 2.1 Dimensions




Figure 2 Dimensions

### 2.2 Layout Dimensions




Figure 3 Layout Dimensions

### 2.3 Antenna performance

Table 1 Antenna performance


Parameter	Specification	Notes
Antenna dimension(mm)	18*18*4	
Operation band	1575.42 ± 1.023 MHz	
Center Frequency	1579MHz±3MHz	With 75.5×38mm GND Plane
Bandwidth	18MHz min	Return Loss@-10dB
Polarization	RHCP	
Axial ratio	Max 3.0dB@zenith	
Impedance	50 Ohm	

## 2.4 Reliability

**Table 2 Reliability**

Items	Requirement
Operating temperature	-40°C to +85°C
Storage temperature	-40°C to +105°C
Environment	RoHS

## 2.5 Antenna S Parameter Data



**Figure 4 S Parameter Data**

## 3 TEST

### 3.1 Test Conditions

Parts shall be measured under a condition (Temp.: $20^{\circ}\text{C} \pm 15^{\circ}\text{C}$ , Humidity:  $65\% \pm 20\%$  R.H.).

### 3.2 Ground Plane Dimension




Figure 5 Ground Plane

### 3.3 Test Jig





Figure 6 Test Jig

## 4 ENVIRONMENTAL TEST

Table 3 ENVIRONMENTAL TEST

NO	Item	Test Condition	Remark
----	------	----------------	--------

6.1	Humidity Test	The device is subjected to 90%~95% relative humidity 60°C± 3°C for 96h~98h, then dry out at 25°C± 5°C and less than 65% relative humidity for 2h~4h. After dry out the device shall satisfy the specification in table 1.	It shall fulfil the specifications in Table 4.
6.2	High Temperature Exposure	The device shall satisfy the specification in table 1 after leaving at 105°C for 96h~98h, provided it would be measured after 2h~4h leaving in 25°C ±5°C and less than 65% relative humidity.	It shall fulfil the specifications in Table 4.
6.3	LOW Temperature	The device shall satisfy the specification in table 1 after leaving at -40°C for 96h~98h, provided it would be measured after 2h~4h leaving in 25°C±5°C and less than 65% relative humidity.	It shall fulfil the specifications in Table 4.
6.4	Temperature Cycle	Subject the device to 40°C for 30 min. followed by a high temperature of 105°C for 30min cycling shall be repeated 5 times. At the room temperature for 1h prior to the measurement.	It shall fulfil the specifications in Table 4.
6.5	Vibration	Subject the device to vibration for 2h each in x y and z axis with the amplitude of 1.5mm, the frequency shall be varied uniformly between the limits of 10Hz~55Hz.	It shall fulfil the specifications in Table 4.
6.6	Soldering Test	Lead terminals are heated up to 350°C±10°C for 5s±0.5s with brand iron and then element shall be measured after being placed in natural conditions for 1h. No visible damage and it shall fulfill the specifications in Table 1	It shall fulfil the specifications in Table 4.
6.7	Solder ability	Lead terminals are immersed in soldering bath of 260°C ~290°C for 3s±0.5s. More than 95% of the terminal surface of the device shall be covered with fresh solder.	The terminals shall be at least95% covered by solder.
6.8	Terminal Pressure Strength	Force of 2kg is applied to each lead in axial direction for 10s±1s (see drawing). No visible damage and it shall fulfill the specifications in Fig 6	Mechanical damage such as breaks shall not occur.




**Figure 7 press test**

**Table 4 Test**

Item	Specification After Test (MHz)
Center frequency change	$\pm 2.0$

## 5 PACKAGE

### 5.1 PACKING



**Figure 8 PACKING**


**Table 5 PACKING**

Name	Quantity
Cushion	20
Package Base	24
Vacuum	4
Inner Box	4
Label	5
Package	1

## 5.2 Disposal information

This device must not be treated as household waste.

For more detailed information about recycling electronic components contact your local waste management authority.



## 6 ORDERING CODES

Table 6 ORDERING CODES

Ordering Number	Category	Application	Features
AGR7104-ES	Antenna	GPS	Ceramic Patch antenna

## 7 REVISION HISTORY

Revision	Date	Author	Status / Comments
V1.0	2019-08-08	Toby	Start version, first released
V2.0	2021-07-21	Toby	



[www.allystar.com](http://www.allystar.com)



info.gnss@allystar.com



5F, Building No.4, Winlead Intelligent Park, No.3, FaDa road  
(middle), Bantian Subdistrict, LongGang District, Shenzhen City,  
Guangdong Province, China.

