


说明:

1. 结构: film+glass+FPC
 film:雾面防牛 (0.18mm)
 glass:500 μ /口 (1.1mm)
 tail:FPC (pitch=1.0mm)
 总厚度: 1.4±0.10mm
2. 工作电压: 5.0V
3. 电路等级: DC5V 1mA
4. 绝缘阻抗: $\geq 20M\Omega$ (25V DC)
5. 线性: $\leq 1.5\%$
6. 透光率: $\geq 80\%$ 表面硬度3H
7. 操作压力: 30-120g
8. 使用寿命: 打点 ≥ 1000000 次;
 画线 ≥ 100000 次 (150g来回算两次)
9. 工作环境: $-10^{\circ}C \sim +60^{\circ}C$, $\leq 90\%RH$
10. 储存环境: $-20^{\circ}C \sim +70^{\circ}C$, $\leq 90\%RH$
11. 回路电阻: X:200-900 Ω Y:200-900 Ω
12. 未注尺寸公差 $\pm 0.3MM$
13. 产品符合“ROHS”

逻辑:



客户确认: _____

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES MILLIMETERS TOLERANCES: ANGLES $\pm 1^{\circ}$.XX" $\pm 0.2^{\circ}$.XXX" $\pm 0.005^{\circ}$ OR 0.Xmm $\pm 0.5mm$ 0.XXmm $\pm 0.13mm$		DATE: DE-DATE		DRAWING NO.:		REV
客户型号:		DATE: CH-DATE		LX-RTP512V1-8.0		
设计:		DATE: APP-DATE		TITLE:		SHEET NO.: 1 OF 1
出图日期: 2021-04-12		TITLE:		TITLE		

TM3006K	DESCRIPTION
---------	-------------