



F **0802** — **XX** **P** **X** **F** **0** **0** **0** **R**

1 2 3 4 5 6 7 8 9 10

UL Style : 2651

Operating Temperature : -20°C to +105°C

Flammability Rating : UL-VW-1

Voltage Rating : 300V

Physical

Insulation Material : Polyvinyl Chloride (PVC)

Conductor : #28AWG (7*0.127) Stranded Tinned Copper

Color : Grey With Red Edge

Electrical

Impedance : 100Ω (Unbalanced)

Capacitance : 14.2 pF/ft.

Inductance : .14μH/ft.

Propagation Delay : 1.43 ns/ft.

Insulation Resistance : 1GΩ/M min.

1. PRODUCTS:
F: Flat Cable
2. SERIES NO.:
0802
3. CONTACT NO.:
10-68
4. INSULATOR MATERIAL:
P: PVC

5. CABLE LENGTH:
A: 100
B: 250
D: 500
6. UNIT:
F: Feet

7. FILL IT WITH '0'

8. FILL IT WITH '0'
9. FILL IT WITH '0'
10. ROHS

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	SCALE 比例 参考	TOLERANCE 容許公差	
DWG. 圖號 HELEN	UNIT 單位 MM	PART NAME 品名	
DATE 制表日 2011/11/24	PAGE 張數 1 OF 1	FLAT CABLE 1.0mm UL2651 GREY COLOR	
		XXP 28AWG ROHS	
		PART NO. 料號 F0802-XXPXF000R	