



PARA LIGHT ELECTRONICS CO., LTD.

11F., No. 8, Jiankang Rd., Zhonghe Dist., New Taipei City 235, Taiwan

Tel: 886-2-2225-3733

Fax: 886-2-2225-4800

E-mail: para@para.com.tw

www.paralighttaiwan.com

DATA SHEET

PART NO.: LT5050UVC-XPCA1

REV: A / 0

CUSTOMER'S APPROVAL: _____

DCC: _____

DRAWING NO.: DS-31P-20-0022

DATE: 2020-06-28

PAGE

1


■ Features

- *SIZE: 5.0*5.0*1.7mm
- *Suitable for all SMT assembly and solder process
- * Available on tape and reel
- * Moisture sensitivity level: Level 5
- * RoHS compliant

■ Applications

- * Ultraviolet disinfection
- * Phototherapy
- * Bio- Analysis/ Detection
- * General use

■ Package Dimensions



Notes:

1. All dimensions are in millimeters.
2. Tolerance is $\pm 0.2\text{mm}$ unless otherwise noted

■ Absolute Maximum Ratings($T_a=25^{\circ}\text{C}$)

| Parameter | Symbol | Rating | Units |
|-----------------------|--------------------|-----------|--------------------|
| Power Dissipation | PD | 4.0 | W |
| Forward Current | IF | 600 | mA |
| Operating Temperature | Topr | -10~ +55 | $^{\circ}\text{C}$ |
| Storage Temperature | Tstg | -30 ~ +85 | $^{\circ}\text{C}$ |
| Junction Temperature | Tj | 90 | $^{\circ}\text{C}$ |
| Thermal Resistance | R _{THJ-S} | 15 | K/W |


Notes:

- 1/10 duty cycle 0.1 ms pulse width
2. The above forward voltage measurement allowance tolerance is $\pm 0.1\text{V}$
3. ESD < 2000V




■ ELECTRO-OPTICAL CHARACTERISTICS : ($T_a = 25^{\circ}\text{C}$)

| Parameter | Symbol | TEST | Min | Typ | Max. | Unit |
|----------------------------|-----------------|----------|-----|-------------|------|---------------|
| Reverse Current | IR | VR=5V | | | 5 | μA |
| Forward Voltage | VF | IF=350mA | | 7.0 | | V |
| Total Radiant Flux | Φ_e | IF=600mA | | 80 | | mW |
| Peak wavelength | λ_p | IF=600mA | | 275 \pm 5 | | nm |
| Spectral Line Half - Width | $\Delta\lambda$ | IF=600mA | | 11 | | nm |
| Half Intensity Angle | 2 θ 1/2 | IF=600mA | | 120 | | deg |

■ Typical Electro-Optical Characteristics




Forward Current Vs Forward Voltage



■ Packaging

Carrier tape dimension



Package: 600pcs/reel

Reel Dimension





Fig.2-2 Reel Dimension

Table 2-1 Reel Dimension

| | |
|---|------------|
| A | 12±0.1mm |
| B | 178±1mm |
| C | 60±1mm |
| D | 13.0±0.5mm |

Notes: The tolerances unless mentioned $\pm 0.1\text{mm}$, Unit: mm

■ SMT Reflow Soldering Instructions



Notes:

1. Reflow soldering should not be done more than two times. If more than 24 hours between the two soldering, LED will be damaged.
2. When soldering, do not put stress on the LEDs during heating.

Soldering iron

1. When do soldering by hand, keep the temperature of iron below less 300C less than 3 seconds
2. Soldering by hand should be done only one time

Repairing

Repairing should not be done after the LEDs have been soldered. When repairing is unavoidable, suitable tools must be used.

It should be confirmed in advance whether the characteristics of LEDs will or not be damaged by repairing.



SURFACE MOUNT DEVICE LED

Part No.: LT5050UVC-XPCA1

REV:A / 0

■ Cautions

1. The encapsulated material of the LEDS is silicone. Therefore the LEDS have a soft surface on the top of package. The pressure to the top surface will be impacted on the reliability of the LEDS. Precautions should be taken to avoid the strong pressure on the encapsulated part. So when use the picking up nozzle, the pressure on the silicone resin should be proper.
2. Components should not be mounted on warped(non co plane)portion of PCB.After soldering,do not warp the circuit board.
3. Do not apply mechanical force or excess vibration during the cooling process to normal temperature after soldering. Do not rapidly cool device after soldering.

■ Handling Precautions

Handle the component along the side surface by using forceps or appropriate tools; Do not directly touch or Handle the silicone lens surface, it may damage the internal circuitry.

■ Storage

| Conditions | | Temperature | Humidity | Time |
|------------|-----------------------------|-------------|----------|-------------------------|
| Storage | Before Opening Aluminum Bag | ≤30°C | ≤75% | Within 1 Year From Date |
| | After Opening Aluminum Bag | ≤30°C | ≤60% | 24hours |
| Baking | | 60±5°C | - | ≥24hours |

Notes

1. If the moisture absorbent material(silica gel) has faded away or the LEDS have exceeded the storage time,baking treatment should be performed after unpacking and based on the following condition(65±5)°C for above 24 hours.
2. If the package is flatulence or damaged, please notify the sales staff to assist.
3. Similar to most Solid state devices;LEDs are sensitive to Electric-Static Discharge(ESD)and Electrical Over Stress(EOS).



SURFACE MOUNT DEVICE LED

Part No.: LT5050UVC-XPCA1

REV:A / 0

● PART NO. SYSTEM :

L - T 3535 UVC - X X X XX

Single chip : Blank
A1 : Double Dice
A2 : Three Dice A3: Four Dice

E : EMC
P: PPA/PCT
C: ceramics

P: Viewing Angle 120 C: Angle 60
Y: Viewing Angle 150 I: Angle 90

Dice Size:
K:20mil M:22mil N: 28mil O: 30mil
R:35mil T: 38mil U:42mil X:45mil

IR1:940nm SURFACE MOUNT DEVICE LED
IR4:850nm SURFACE MOUNT DEVICE LED
UVC:200-280nm UVB:280-315nm
UVA:315-400nm

3535 3.5*3.5mm
5050 5.0*5.0mm

T :PLCC Top View Type