

XNCJH52M000TJEA0P0







< List of part numbers with package codes >

XNCJH52M000TJEA0P0



Appearance & Shape







Based on long experience and activity, Murata's Crystal Oscillator consists of high quality quartz crystal unit and excellent temperature compensation circuit, which are packaged with high circuit technology and high adjusting technology. They are suitable for communication equipment, business radios, GPS(GNSS) system and survey equipment.



Applications

Other Usage

Industrial



Packaging Information

Packaging	Specifications	Minimum Order Quantity
P0	180mm Plastic Tape	3 0 0 0

1 of 3

Atten ti o n



URL: http://www.murata.com/

Lastupdated 2015/11/12



XNCJH52M000TJEA0P0

Specifications

Shape	S M D
Frequency	52.0000MHz
Frequency Tolerance	±1ppmmax. (25±3°C)
Operating Temperature Range	-30 °C to 85 °C
Frequency Shift by Temperature	±0.5ppmmax.
Frequency Aging	±1ppmmax./year
Supply Voltage	+3.0±5%
Current Consumption(Max.)	2 m A
Output Voltage	0.8Vp-p / min.
Load Impedance/Capacitance	(10Kohm//10pF)±10%

2 of 3



Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please sheek with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

