



3	BRASS	SURFACE:TIN PLATED<REFLOW FINISH>1μm min UNDER PLATING:COPPER 0.3μm min		8	PS	REINFORCEMENT COLLAR
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATED 0.2μm min		7	PS	BLACK<PLASTIC REEL>
		LEAD AREA:TIN PLATED 1μm min		6	POLYIMIDE	BROWN<HEAT-RESISTANCE TAPE>
		UNDER PLATING:NICKEL 0.3μm min		5	POLYESTER	CLEAR<COVER TAPE>
1	POLYAMIDE	BEIGE, UL94V-0		4	PS	CLEAR<EMBOSSED CARRIER TAPE>
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE 5 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : KH. IKEDA		11. 12. 28	DRAWING NO.	EDC3-341296-02		
		CHECKED : AR. TAKAHASHI		11. 12. 28	PART NO.	DF9- * S-1V<69>		
		DESIGNED : SH. HOSODA		11. 12. 27	CODE NO.	CL540-		
		DRAWN : KR. AJITO		11. 12. 27	 			



NOTES 4 : 1 REEL 1000 CONNECTORS.

5 : AT THE BEGINNING OF THE REEL,
30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL,
20 COMPONENTS SHALL BE EMPTY.

6 LET THE SENDING HOLE OF 9 TO 21 CONTACTS
BE ONLY THE UPPER ONE SIDE TOWARD A DRAWING.
THE SENDING HOLE OF 23 OR MORE CONTACTS
IS ESTABLISHED IN BOTH SIDES, AS SHOWN IN A FIGURE.

7 A POCKET SHAPE IS DIFFERET AT INTERVALS OF EACH
CAVITY NUMBER TO AVOID OVERLAP.

8 : PEEL FORCE REFERS TO JIS C 0806.

9 AFTER PACKING, ROLL 2 METERS OF THE REINFORCEMENT
COLLAR TO OUTER CIRCUMFERENCE OF TAPE AND REEL
POCKET, AND TAPE DOWN AT THE END THE COLLAR.

	DRAWING NO.	EDC3-341296-02		
	PART NO.	DF9-*S-1V(69)		
	CODE NO.	CL540-		2 2