



注：配件扭在FAKRA接头上

Requirements:

1. The outer layer of the wire is free from skin damage or damage
2. The finished product must be 100% tested for continuity and OK
3. The finished product must undergo 100% full inspection OK
4. Adopting an environmentally friendly process that meets ROHS requirements
5. Terminal/connector tension: 1.5KG~
6. For unmarked tolerances, please refer to the general tolerances

RoHS Compliant

5	HEAT SHRINK SLEEVE	—	BLACK HEAT SHRINK SLEEVE $\phi 3.5 \times 20\text{mm}$	2	—
4	PLUG	—	SMB 接头	1	—
3	CONN	—	FAKRA—C BLUE	1	—
2	CONN	—	MMCX弯公头	1	—
1	WIRE	—	RG178 COLOR BROWN	1	A/R
ITEM	PART No.	VENDOR	DESCRIPTION	Q'TY	OVERALL WIRE LENGTH

PIN ASSIGNMENT

③			
②			
①			
SYM	NAME	DATE	REVISIONS

MATERIAL SPECIFICATION

DRAWN BY	CHECKED BY	APPROVED BY	CONFIRMED BY	DESCRIPTION	群翰电子有限公司 CviLux Corporation		CUST. CODE
Li jing	Iron	Iron	Waleed	FAKRA CABLE	DRAWING No.	CviLux P/N	TCF0821
07/12.23'	07/12.23'	07/12.23'	07/12.23'	SHEET: 1 OF 1	WQ230020DA	DH-23Q50020	CUSTOMER P/N
							—