



ALL DIMENSIONS ARE IN MM
COMMON TOLERANCE : ± 0.15

GENERAL INFORMATION

1. Lens material-Optical PC
2. Operating Temperature rang; (40 to +100)deg.Upper limit ; +130 deg
3. Storage tempereture range; (40 to +100)deg.Upper limit; +130 deg.

Average transmittance in visible spectrum 400nm-700nm > 90%

Usage and Maintenance

1. If necessary ,clean lenses with mild soap,water and soft cloth.
2. Never use any commercial cleaning solvents like alcohol.
3. Handel and install lenses with wearing gloves.
4. skin oils may damage lenses or its optical characteristics

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 9001:2015 Class M3 and applies if not otherwise shown in the drawing.

		DEBURE & BREAK SHARP EGGES	DO NOT SCALE DRAWING		REVISION	REMARK.
	NAME	SIGNATURE	DATE	OPTIKS MECHATRONICS INDIA PVT.LTD		
DRAWN	ABHISHT		11-10-2022	PART NAME	24X1_5050_60°	
CHECKED	DEVESH		11-10-2022	DRAWING NUMBER	OMPL-539_REV00	
APPROVED	Pradyumna shandilya		11-10-2022	PART NUMBER	OMPL-539_5050_24X1_60°	
MATERIAL		POLYCARBONATE		SCALE :		
WEIGHT		50.1 gms		FIRST ANGLE PROJECTION		
						This Drawing Is a Property Of Optiks Mechatronics Pvt.Ltd. It May Not Be Copied Or Otherwise Distributed Without Written Permission