



Specifications

Electrical

Voltage Rating: 250V(AC)
 Current Rating: 7A
 Contact Resistance: 20m Ω max.
 Dielectric Withstanding Voltage: 1500V AC/1min.
 Insulation Resistance: 1000M Ω min.

Material

Circuits: 2~10,12
 Insulator: Nylon 66 UL 94V-2
 Color: Natural
 Contact: Brass 1.14mm(0.45 ") Square Wire Pins
 Plating: Tin or Gold Plated
 Temperature Range: -25 °C~+85 °C

Poles	Dimension	
	A	B
2	5.08	10.22
3	10.16	15.30
4	15.24	20.38
5	20.32	25.46
6	25.40	30.54
7	30.48	35.62
8	35.56	40.70
9	40.64	45.78
10	45.72	50.86
12	55.88	60.96

RECOMMENDED P.C. BOARD HOLE DIM.

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 HELEN DATE 制表日 2010/8/30	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE 容許公差 0 ± 0.5 .00 ± 0.3 ANG. ± SIZE 線規尺寸 A4 REV. 版本 A	PART NAME 品名 5.08mm WAFER STRAIGHT TYPE 1X??P W/ LOCKING RIB TIN PLATING WHITE COLOR (V2) ROHS LOW-LEW PART NO. 料號 W4508-XXPSYTW0R