

CKANPLUS SBE-3120-U

The Ckanplus' Big eye series point-of-sale hands free/presentation scanner is the perfect blend of affordability, performance and style. scale commercial deployment.



With the SBE-3120, retailers no longer have to compromise their budgets to get performance and a modern design. Get it all with Ckanplus' SBE-2100.

The SBE-3120 is also suitable for various environments such as manufacturing, healthcare, and retail POS.

Make scanning faster and easier!

Product Features:



With a high-speed processor and resolution camera, Integrating Ckanplus' advanced decoding technology, it quickly and accurately reads all kinds of barcodes, boosting



With Ckanplus' intelligent software tools, the configuration and installation process can be simplified.



Easy to be compatible with various POS machines and devices, making it convenient to use.

Physical Characteristics:

Dimensions: 109.4mm x 153.3mm x101.8mm

Voltage:5V

Weight: 297.5g

Performance:

Starting Current:	430mA	
Stand-by Current	240mA	
Operating current	430mA	
Image (Pixels)	Main:640*480; Secondary:640*480	
Exposure mode	Global shutter	
Light Source	(Illumination)Red color LED	
Field of View	Main:39°(Horizontal),29°(Vertical); Secondary:56°(Horizontal),44°(Vertical);	
Print Contrast	20% minimum	
Motion Tolerances	3.0m/s	
Minimum Resolution	≥4mil	
DOF (depth of field)	Code39(5mil)	0mm-80mm
	Code39(13mil)	0mm-180mm
	PDF417: 6.7mil	0mm-80mm
	QR code(20mil)	0mm-100mm
	UPC-A(13mil)	0mm-170mm
Designed to withstand drops	1.2m	
Operating Temperature	Range:-20°C to 60°C	
Interface	USB/USB COM	
IP	IP42	

Decode Capability:

1D: Codabar、Code 39、Code 32 Pharmaceutical (PARAF)、Interleaved 2 of 5、NEC 2 of 5、Code 93、Straight 2 of 5 Industrial、Straight 2 of 5 IATA、Matrix 2 of 5、Code 11、Code 128、GS1-128、UPC-A、UPC-E、EAN/JAN-8、EAN/JAN-13、MSI、GS1 DataBar Omnidirectional、GS1 DataBar Limited、GS1 DataBar Expanded、China Post(Hong Kong 2 of 5)、Korea Post.

2D: Codeblock A、Codeblock F、PDF417、Micro PDF417、GS1 Composite Codes、QR Code、Data Matrix、MaxiCode、Aztec、HANXIN

User Environment:

Operating Temperature : -20°C to 60°C

Storage Temperature : -30°C to 70°C

Humidity : 5% to 95% relative humidity, non-condensing

Shock Specifications : Designed to withstand 1.2m(5') drops

Ambient Light Immunity : 0-100,000 Lux.

Dimension (unit:mm)

