



RECOMMENDED  
CABLE STRIPPING DIM'S  
(建議剝線尺寸)

- NOTE: FINISH(PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. NICKEL PL 70 MIN THICK OVER COPPER STRIKE
  3. GOLD PL 3 MIN OVER NICKEL PL 70 MIN THICK OVER COPPER STRIKE
  4. ZINC DIECAST
  5. BRASS PER QQ-B-613

UNLESS OTHERWISE SPECIFIED  
GENERAL TOLERANCES  
0.5~6 = ±0.2  
>6~30 = ±0.4  
>30~120 = ±0.6

8	NUT	1	NOTE 4	NOTE 2			
7	WASHER	1	NOTE 5	NOTE 2			
6	GASKET	1	RUBBER	ORANGE			
5	BRAID HOLDER	1	NOTE 1	NOTE 2			
4	CONTACT PIN	1	NOTE 1	NOTE 3			
3	LOCK RING	1	NOTE 1	NOTE 2			
2	INSULATOR	1	DELIN	WHITE			
1	BODY	1	NOTE 1	NOTE 2			
NO.	DESCRIPTION	QTY	MATERIAL	SPECIFICATION			REMARK
DRAW BY	周曉君	090108	SCALE	1 : 3	PROJ		ITEM NO. TL4217-58-BDNG
DEGN BY	YANG		UNIT	MM			TITLE BNC CLAMP JACK (FOR RG-58/U.58/U)
APPD BY	RAY						DRAWING NO. TL4217-58-BDNG-1N05-C

DATE DRAWNG BY REVISED

同利企業有限公司 TELE LONG ENTERPRISE CO.,LTD