

FG621-EA LTE Module

Perfect Wireless Experience

FG621-EA LTE Module Technical Specifications

Product Features

- LTE Category: Cat6
- FDD: B1,B3,B5,B7,B8,B20,B28,B32 TDD: B38,B40,B41
- WCDMA: B1,B3,B5,B8
- LGA: 37.0*39.5*2.8 mm
- Operating Temperature: -30~+75°C
- Storage Temperature: -40~+85°C
- Operating Voltage: 3.3V~4.4V, Typical 3.8V
- AT Command Set: 3GPP TS 27.007 and 27.005, proprietary FIBOCOM AT commands
- TX Power: 23dBm

Data

- LTE FDD CA: 300Mbps DL/50Mbps UL
- LTE TDD CA: 226Mbps DL/30Mbps UL
- UMTS: 384 kbps DL/384 kbps UL
- HSPA/HSPA+: 42Mbps DL/11Mbps UL



Interface

- SIM Card: 1.8V/3.0V
- USB2.0
- I2C
- PCM/Digital Audio
- GPIO
- SPI
- Antenna : Main/Div

Function

- SMS : MO/MT Text and PDU modes
- DHCP/TCP*/UDP*/HTTP(S)*/FTP(S)*/SSL*
- PPP/ECM/RNDIS
- DFOTA
- VoLTE/PCM/Recording*/TTS*/BIP/FFS*/LBS*
- Cell ID
- Note: TTS has copyright fee

Driver

- Linux/ Android*/Windows*

Approval

- CE*/GCF *
- RoHS/HF*
- Carriers: TBD

Note*: in planning

Copyright © Fibocom Wireless Inc. | Subject to changes in technology, design and availability | E-mail : market@fibocom.com | Tel : +86 755-2673 3555