


逻辑:



客户确认: _____

说明:

1. 结构: film+glass+FPC

film:雾面防牛 (0.188mm)

glass:500Ω/□ (1.8mm)

tail:FPC (pitch=1.0mm)

总厚度: 2.1±0.10mm

2. 工作电压: 5.0V

3. 电路等级: DC5V 1mA

4. 绝缘阻抗: ≥20MΩ (25V DC)

5. 线性: ≤1.5%

6. 透光率: ≥80%

7. 操作压力: 10-100g

8. 使用寿命: ≥1,000,000次

9. 工作环境: -10℃~+60℃, ≤90%RH

10. 储存环境: -20℃~+70℃, ≤90%RH

11. 未注尺寸公差按±0.20

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES MILLIMETERS TOLERANCES: ANGLES ±1° .XX" ±.02" .XXX" ±.005" OR 0.Xmm ±0.5mm 0.XXmm ±0.13mm			
客户型号:	DATE: DE-DATE	DRAWING NO.:	REV
设计: XXY	DATE: CH-DATE	LX-TPM330-12.1	REV
出图日期: 2015-01-21	DATE: APP-DATE	TITLE: TITLE	SHEET NO.: 1 OF 1

SKGY3007K

DESCRIPTION