



Section A-A



Section B-B



Section C-C

T 4000 - S F B A J 0 0 0 R

- | | | |
|---|--|--|
| 1. PRODUCTS:
T:Terminal | 5. MATERIAL:
B:Brass | 7. WIRE OPTION:
I:Suitable For
22-26 Awg |
| 2. SERIES NO.:
4000 | 6. TERMINAL OPTION:
A:Female Terminal for
1x1P-1x14P/2x1P-2x7P | J:Suitable For
22-28 Awg |
| 3. CONTACT PLATING:
T: Tin
S: Selective Gold
G: Gold Flash | B: Female Terminal for
1x15P-1x30P/2x8P-2x29P | 8. FILL IT WITH "0" |
| 4. CONTACT TYPE:
F: Female | | 9. FILL IT WITH "0" |
| | | 10. FILL IT WITH "0" |
| | | 11. R: ROHS |

Specifications & Ordering Information:

Part No	Thickness	Material	Wire Range	Insulation O.D.	Finish	Qty/reel
T4000-SFBAJ000R	0.2	Brass	AWG #22~28	1.6-1.2 mm	Selective Gold Flash	10,000PCS
T4000-TFBAJ000R	0.2	Brass	AWG #22~28	1.6-1.2 mm	Pre. Tin-Plated	10,000PCS

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE : .000 : ±0.08 .00 : ±0.13 .0 : ±0.25
DWG. 製圖 BETTY		PART NAME 品名 DUPOND 2.54mm TERMINAL BRASS MATERIAL SUITABLE AWG22-28 1R=10K PCS STANDARD TYPE (less than 1X14P & 2X7P use this type)
DATE 制表日 2009/08/14	REV. 版次 A	PART NO. 料號 T4000-XFBAJ000R