

Note: This datasheet may be out of date

Please download the latest datasheet of PKMCS1818E20A0-R1 from the official website of Murata

Manufacturing Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=PKMCS1818E20A0-R1

### PKMCS1818E20A0-R1










### Appearance & Shape







### **Features**

Taking advantage of extensive acoustic and mechanical design technology and high performance ceramics, Murata has developed High Sound Pressure Level SMD piezoelectric sounder that is suitable for the burglar alarm and notification sound on the equipments inside vehicles.

It helps the thin, high-density design of electronic equipment.

#### Features

- 1. High sound pressure level and clear sound
- 2. Available for a wide temperature range(-40 ~ +105 °C).
- 3. Reflowable
- 4. Tape & Reel supply



Automotive Usage	Infotainment
Other Usage	Automotive/Industrial



# Packaging Information

Packaging	Specifications	Minimum Order Quantity
-R1	330mm Embossed Tape	250

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/10/05



Note: This datasheet may be out of date.  $\underline{ \text{Please download the latest datasheet of PKMCS1818E20A0-R1 from the official website of Murata} \\$ 

Manufacturing Co., Ltd. https://www.murata.com/en-global/products/productdetail?partno=PKMCS1818E20A0-R1

# PKMCS1818E20A0-R1



Size	18.0×18.0×8.0 mm	
Frequency	2.0kHz	
Sound Pressure Level	100dB (typ.)	
Sound Pressure Level	90dB (min.)	
Measure Condition of Sound Pressure Level	[12Vo-p,2.0kHz,square wave,10cm]	
Maximum input voltage	18.0Vo-р [with polarity]	
Operating Temperature Range	-40°C to 105°C	
Storage Temperature Range	-40°C to 105°C	
Shape	SMD	
Drive Type	External Drive	

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/


Last updated :2019/10/05

Note: This datasheet may be out of date  $\underline{ \text{Please download the latest datasheet of PKMCS1818E20A0-R1 from the official website of Murata} \\$ 

Manufacturing Co., Ltd.
https://www.murata.com/en-global/products/productdetail?partno=PKMCS1818E20A0-R1

# PKMCS1818E20A0-R1





Frequency Response

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/