



- Notes:
- 1.Type:Film to Glass
 - 2.Operating Voltage: $\leq 10v$
 - 3.Operation Temperature: $-20^{\circ}C \sim 65^{\circ}C$
Storage Temperature: $-30^{\circ}C \sim 70^{\circ}C$
 - 4.Life Time:1,000,000 times
 - 5.Connect Material:FPC
 - 6.Response Time: $\leq 10ms$
 - 7.Linearity: $\leq 1.5\%$
 - 8.Transmittance: $\geq 75\%$
 - 9.Surface Hardness: $\geq 3H$ (pencil)
 - 10.Operation force: $60g \sim 150g$

- 11.Insulation: $\geq 20M\Omega$
- 12.Resistance: $50\Omega < PIN1, PIN2 < 250\Omega$
 $50\Omega < PIN2, PIN4 < 250\Omega$
 $50\Omega < PIN4, PIN5 < 250\Omega$
 $50\Omega < PIN5, PIN1 < 250\Omega$

TOLERANCES
(UNLESS OTHERWISE STATED)

DECIMALS	ANGLES	$\pm 0.5^{\circ}$
$>2000/M$	$\pm 2.00/M$	
$1600 < X \leq 2000/M$	$\pm 1.20/M$	
$1200 < X \leq 1600/M$	$\pm 0.80/M$	
$800 < X \leq 1200/M$	$\pm 0.50/M$	
$400 < X \leq 800/M$	$\pm 0.40/M$	
$120 < X \leq 400/M$	$\pm 0.30/M$	
$30 < X \leq 120/M$	$\pm 0.20/M$	
$< 30/M$	$\pm 0.10/M$	

Model No.:	GT-SW-215A-1	Size	21.5"	Ratio	16:9
Structure	G+F	Unit	mm	Scale	1:1
Design	李俊	Date	2015.8.5	Page	1/1
Check	付特飞	Date	2015.8.5	Version	AD
Release	江基	Date	2015.8.5		