

MC-28AA-XXX-H-1812-B COB Datasheet

Applications

- Spot lighting
- Down lighting
- Recessed fixtures
- Can lighting




Naming Conventions

MC - 28AA - XXX - H - 1812 - B
 (1) (2) (3) (4)

- (1) COB Series
- (2) CCT Range
- (3) CRI Range
- (4) Chip Array: 18 series, 12 parallel

Package Dimensions



1. All dimensions in millimeters.
2. Tolerance is ± 0.3 mm unless otherwise noted.
3. The information in this document is subject to change without notice.

Absolute Maximum Ratings

Item	Symbol	Absolute Maximum Rating	Unit
Forward current	If	2760	mA
Reverse Current	Ir	1	mA
Peak Power	-	146.8	W
Operating Temperature	Topr	-30~85	°C
Storage Temperature	Tstg	-40~100	°C
Hand soldering condition	Tsld	3.5sec@350°C	sec
Case Temperature	Tc	105	°C
LED Junction Temperature	Tj	125	°C
Temperature of central silicon Surface	Ts	125@IRDA Test	°C


Characteristics (Tc=25°C)

Part Number	Nominal CCT	CRI(Ra)		Luminous flux (lm)		Forward Current (mA)	Voltage (V)			Thermal Resistance Rj-c (°C/W)
		Min.	Typ.	Min.	Typ.		Min.	Typ.	Max.	
MC-28AA-270-H-1812-B	2700K	80	82	8970	9967	1440	50.4	61.2	0.32	
MC-28AA-300-H-1812-B	3000K			9440	10492					
MC-28AA-400-H-1812-B	4000K			9730	10807					
MC-28AA-500-H-1812-B	5000K			10000	11122					
MC-28AA-570-H-1812-B	5700K			10060	11174					

Notes:

- Luminous flux is measured with an accuracy of +/- 5 %.
- CRI is measured with an accuracy of +/- 1
- Some color and CRI bins may have limited availability, please contact us before ordering.
- All measurements were made under the standardized environment of Shineon.

Chromaticity Characteristics (Tc=25°C, If=1440mA)




BIN CODE	CCT	Color Coordinates(x,y)				
		Center		Oval parameter		
		x	y	a	b	Theta°
273	2700K (3-step)	0.4578	0.4101	0.00774	0.00411	57.28
303	3000K (3-step)	0.4338	0.403	0.00834	0.00408	53.17
403	4000K (3-step)	0.3818	0.3797	0.0094	0.004	54
503	5000K (3-step)	0.3447	0.3553	0.00822	0.00354	59.62

Notes:

1. 5% tolerance for luminous intensity may be caused by measurement inaccuracy.
2. Measurement Uncertainty of the Forward Voltage : +/-3%
3. Chromaticity coordinate bins are measured with an accuracy of +/-0.005.

Chromaticity Characteristics (Tc=25°C, If=1440mA)




BIN CODE	CCT	Color Coordinates(x,y)				
		Center		Oval parameter		
575A	5700K (5-step)	x	y	a	b	Theta°
			0.3287	0.3417	0.01243	0.00533
575B	5700K (5-step)	Cuttingline			x	y
				Point1	0.3227	0.3417
				Point2	0.3347	0.3417


Notes:

1. 5% tolerance for luminous intensity may be caused by measurement inaccuracy.
2. Measurement Uncertainty of the Forward Voltage : +/-3%
3. Chromaticity coordinate bins are measured with an accuracy of +/-0.005.


Typical Relative Spectral Power Distribution (Tc=25°C, If=1440mA)




Typical Spatial Distribution (Tc=25°C, If=1440mA)




Forward Current vs. Forward Voltage
($T_c=25^\circ\text{C}$)




Forward Current vs. Relative Luminous Flux
($T_c=25^\circ\text{C}$)




Case Temperature vs. Forward Voltage
($I_f=1440\text{mA}$)



Case Temperature vs. Relative Radiant Flux
($I_f=1440\text{mA}$)



Case Temperature vs. Allowable Forward Current



Reliability

(1)Details of the tests

No.	Test Item	Reference Standard	Test Condition	Test Duration	Defective	Sample Size
1	High Temperature Operating Life	JESD22-A108	Tc=85°C, Typical IF	1000hr	0	10
2	Low Temperature Operating Life	JESD22-A108	Ta=-40°C, Typical IF	1000hr	0	10
3	Temperature Shock	MIL-STD-202G Method 107G	-40°C ↔ 100°C	100cycles	0	10
4	High Temperature Storage	JESD22-A103	100°C	1000hr	0	10
5	Temperature Humidity Storage	JEITA ED-4701 100 103	60°C, 90%RH	1000hr	0	10

(2)Judgment Criteria of Failure for Reliability Test

(Ta=25°C)

NO.	Measuring Item	Symbol	Measuring Condition	Judgment Criteria for Failure
1	Forward Voltage	Vf	IF=1440mA	>U X 1.1
2	Total Luminous Flux	∅v	IF=1440mA	<S X 0.85

Notes:

U defines the upper limit of the specified characteristics. S defines the initial value.

PACKING

