

2835A03-XXS05-2P-F19-EC-LX Datasheet

This 2835 LED Light Source is a high performance energy efficient device which can handle high thermal and high driving current. The small package outline and high intensity make it an ideal choice for LED panel light, LED bulb light, LED tube light, backlighting and etc.



The White Power LED is available in the range of color temperature from 2600K to 7000K.

This part has a foot print that is compatible to most of the same size LED in the market today.

FEATURES

- Available in Cool White, Neutral White and Warm White color
- ANSI-compatible chromaticity bins
- High luminous Intensity and high efficiency
- Low thermal resistance
- Long operation life
- Wide viewing angle at 120°
- Silicone encapsulation/
- Environmental friendly, RoHS compliance

APPLICATIONS


- Flat panel light
- LED tube light
- LED bulb light/
- Decorative and landscape lighting
- Signage and channel letter
- Reading lamp
- Table lamp

Note: The information in this document is subject to change without notice.


2835A03-XXS05-2P-F19-EC-LX

2835	A	03	XX	H	05	2P	Fx	
Package size	LM-80 report type	voltage	CCT	Ra	power	quantity of chips	Program code	
2835	A:General report B:Individual report	03 : 3V 06 : 6V 09 : 9V 18 : 18V	2700	L:<70	02 :0.2W	1S : 1 chip		
3030			3000	N:>70	05 :0.5W	2S : 2 chips in series		
4014			3500	H:>80	10 :1W	2P : 2 chips in		
5050			4000	S:>90		parallel		
5630			5000	E:>95		3S : 3 chips in series		
5730				5700				
				6000				
		6500						

PACKAGE DIMENSIONS



Recommended Solder Pad Design



Notes/ :

1. All dimensions in millimeters
2. Thickness tolerance of copper plate is $\pm 0.02\text{mm}$.
3. Thickness tolerance of product is $\pm 0.05\text{mm}$.
4. Tolerance is $\pm 0.1\text{mm}$ unless otherwise noted.

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Forward current	IF	300	mA
Peak Forward Current	IFP	500	mA
Reverse Voltage	VR	5	V
Power Dissipation	Pd	500	mW
Operating Temperature	Topr	-40~+85	°C
Storage Temperature	Tstg	-40~+100	°C
Soldering Temperature	Tsld	Reflow Soldering: 260°C for 10 seconds	
LED Junction Temperature	Tj	115	°C


ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V _F	IF=150mA	2.7	--	3.0	V
Viewing Angle	2θ _{1/2}	IF=150mA	--	120	--	deg.
Luminous Flux	Φ _v	IF=150mA	58	--	73	lm
Color Rendering Index	CRI	IF=150mA	90	--	--	--
Color Temperature	CCT	IF=150mA	2600	--	7000	K
Thermal Resistance	R _{th-js}	IF=150mA	--	20	--	°C/W


Notes 注:

1. Luminous flux is measured with an accuracy of $\pm 5\%$.
2. Chromaticity coordinate bins are measured with an accuracy of ± 0.01 .
3. CRI is measured with an accuracy of ± 2 .
4. Some color and CRI bins may have limited availability, please contact us before ordering.
5. All measurements were made under the standardized environment of Shineon


RELATIVE SPECTRAL POWER DISTRIBUTION ($T_j = 25^\circ\text{C}$)




TYPICAL SPATIAL DISTRIBUTION




RELATIVE LUMINOUS FLUX VS. CURRENT ($T_j = 25^\circ\text{C}$)




ELECTRICAL CHARACTERISTICS ($T_j = 25^\circ\text{C}$)



MAXIUM CURRENT VS. AMBIENT TEMPERATURE



RELATIVE RADIANT FLUX VS. JUNCTION TEMPERATURE



SORTING RANKS

(1) Luminous Flux $T_j=25^{\circ}\text{C}$

Part Number	Condition	Rank	Unit
2835A03-27S05-2P-F19-EC-LX	150mA	P20	lm
		58-63	
2835A03-30S05-2P-F19-EC-LX		P23	
		63-68	
2835A03-35S05-2P-F19-EC-LX		P3	
		65-70	
2835A03-40S05-2P-F19-EC-LX		P33	
		68-73	
2835A03-50S05-2P-F19-EC-LX		P33	
		68-73	
2835A03-57S05-2P-F19-EC-LX		P33	
		68-73	
2835A03-65S05-2P-F19-EC-LX		P33	
		68-73	

(2) Forward Voltage $T_j=25^{\circ}\text{C}$

Rank	Condition	Min.	Max.	Unit
A7	150mA	2.7	2.8	V
A8		2.8	2.9	
A9		2.9	3.0	


Notes 注：

1. 5% tolerance for luminous intensity may be caused by measurement inaccuracy.


2. Measurement Uncertainty of the Forward Voltage : ± 0.1

(3) Chromaticity Bins


Part Number	2835A03-27S05-2P-F19-LX			CCT	2700K
Bin Code	Color Coordinates(x,y)				
SDCM	x	y	a	b	Theta°
27-3	0.4578	0.4101	0.00810	0.0042	53.7000
27-5			0.01350	0.0070	




Part Number	2835A03-30S05-2P-F19-LX			CCT	3000K
Bin Code	Color Coordinates(x,y)				
SDCM	x	y	a	b	Theta°
30-3	0.4338	0.403	0.00834	0.00408	53.2200
30-5			0.0139	0.0068	




Part Number	2835A03-35S05-2P-F19-LX			CCT	3500K
Bin Code	Color Coordinates(x,y)				
SDCM	x	y	a	b	Theta°
35-3	0.4073	0.3917	0.00927	0.00414	54
35-5			0.01545	0.0069	




Part Number	2835A03-40S05-2P-F19-LX			CCT	4000K
Bin Code	Color Coordinates(x,y)				
SDCM	x	y	a	b	Theta°
40-3	0.3818	0.3797	0.00939	0.00402	53.2200
40-5			0.01565	0.0067	




Part Number	2835A03-50S05-2P-F19-LX			CCT	5000K
Bin Code	Color Coordinates(x,y)				
SDCM	x	y	a	b	Theta°
50-3	0.3447	0.3553	0.00822	0.00354	59.62
50-5			0.0137	0.0059	




Part Number	2835A03-57S05-2P-F19-LX			CCT	5700K
Bin Code	Color Coordinates(x,y)				
SDCM	x	y	a	b	Theta°
57-3	0.3287	0.3417	0.00746	0.00312	59.09
57-5			0.01243	0.00533	



Part Number	2835A03-65S05-2P-F19-LX			CCT	6500K
Bin Code	Color Coordinates(x,y)				
SDCM	x	y	a	b	Theta°
65-3	0.3123	0.3282	0.00669	0.00285	58.57
65-5			0.01115	0.00475	



TAPE AND REEL




Note: The tolerances unless mentioned is ± 0.1 mm, Unit=mm

Notes注:


- (1) Quantity : 4,000pcs/Reel
- (2) Cumulative Tolerance : Cumulative Tolerance/10 pitches to be ± 0.2 mm
- (3) Adhesion Strength of Cover Tape : Adhesion strength to be 0.1-0.7N when the cover tape is turned off from the carrier tape at the angle of 10° to the carrier tape
- (4) Package : P/N, Manufacturing data Code No. and quantity to be indicated on a damp proof Package.

PACKAGING


Name:	PrdtName	 
		
Lot NO:	LotNo	
		
BinCode:	BinCode	
		
IF:	IF	Prd No:  Cus No: CUS_No Quantity: QtyPCS
VF:	VFV	
IV:	IVM	
RA:	RA	
CCT:	CCT	




REEL



moisture-proof bag



desiccant



Outside box
Maximums 48 Reels



Reliability Test Items

Test Items 测试项目	Test Duration 测试时长	Number of Damaged 不良数
Steady State Operating Life of High Temperature (HTOL) $T_s=85^{\circ}\text{C}$, $I_F=\text{Max}$	1000hrs	0/20
Steady State Operating Life of Low Temperature (LTOL) $T_a=-40^{\circ}\text{C}$, $I_F=\text{Max}$	1000hrs	0/20
Pulse Wet Operating Life of High Temperature (PWHTOL) $60^{\circ}\text{C}/90\%\text{RH}$, $I_F 30\text{mins ON}/30\text{min OFF}$	500hrs	0/20
High Temperature Storage (HTS) 100°C	1000hrs	0/20
Low Temperature Storage (LTS) -40°C	1000hrs	0/20
Thermal Shock (TS) $-45^{\circ}\text{C}\sim 125^{\circ}\text{C}$ 15min dwell 30sec transfer	100cycles	0/20
Solder Resistance (SR) 265°C , 3X MSL	5sec	0/20
Solder Ability (SA) 245°C 5sec, 95% coverage	5sec	0/11

Item	Symbol	Test Condition	Criteria for Judgment	
			Min.	Max.
Forward Voltage	V_f	$I_F=\text{Typical Current}$		U.S.L x1.1
Luminous Flux	I_m	$I_F=\text{Typical Current}$	L.S.L x0.7	
CCX&CCY	x,y	$I_F=\text{Typical Current}$		Shift<0.02

REFLOW SOLDERING CHARACTERISTICS



For Reflow Process :

Preheating : 140°C~160°C±5°C, within 2 minutes.

Operation heating: 260°C(Max.) within 10 seconds.(Max)

Gradual Cooling (Avoid quenching).

Lead solder		Lead-free solder	
Pre-heat	120-150°C	Pre-heat	150-200°C
Pre-heat time	120 sec.Max.	Pre-heat time	120 sec.Max.
Peak Temperature	240°C Max.	Peak Temperature	260°C Max.
Soldering time condition	10 sec.Max.	Soldering time condition	10 sec.Max.

 Lead Solder 2.5~5 °C / sec. Pre-heating 120~150 °C 120sec. Max. 240 °C Max. 10 sec. Max. 60sec. Max. Above 200 °C		 Lead-free Solder 1~5 °C / sec. Pre-heating 150~200 °C 120sec. Max. 260 °C Max. 10 sec. Max. 60sec. Max. Above 220 °C	
--	--	--	--

Notes:

The encapsulated material of the LEDs is silicone . Therefore the LEDs have a soft surface on the top of package. The pressure to the top surface will be influence to the reliability of the LEDs. Precautions should be taken to avoid the strong pressure on the encapsulated part. So when using the picking up nozzle, the pressure on the silicone resin should be proper.

PRECAUTION FOR USE

- (1) This device should not be used in any type of fluid such as water, oil, organic solvent, etc.
When washing is required, IPA should be used.
- (2) When the LEDs are illuminating, operating current should be decided after considering the ambient maximum temperature.
- (3) LEDs must be stored to maintain a clean atmosphere. If the LEDs are stored for 3months or more after being shipped from ShineOn, a sealed container with a nitrogen atmosphere should be used for storage.
- (4) The LEDs must be used within seven days after opening the moisture proof packing.
Repack unused Products with anti-moisture packing, fold to close any opening and then store in a dry place.
- (5) The appearance and specifications of the product may be modified for improvement without notice.
- (6) This LED is sensitive to the static electricity and surge. It is recommended to use a wrist Band or anti-electrostatic glove when handling the LEDs.
- (7) On manual soldering, a solder tip must be needed as grounded for usage. If over voltage which exceeds the absolute maximum rating is applied to LEDs, it will cause damage LEDs and result in destruction. Damaged LEDs will show some unusual characteristics such as leak current remarkably increase ,turn-on voltage becomes lower and the LEDs get unlighted at low current.