

ARCA 302015W



Sample photo

Order symbol: ARCA 302015W
Product nbr: 8120122
Description: Cabinet, PC
Remarks: Cover with window, 1-point locking

EAN: 6418074079916
EI. number:
 Finland: 3423190
 Electric No. 8212091786
 Denmark:
 Electric No. Sweden: 2500138

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.

Dimensions:	Length	Width	Height	Accessories:
mm:	300	200	150	MPP ARCA 3020
inch:	11.8	7.9	5.9	MPMP ARCA 3020

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	RAL 7035 -light grey
Gasket material:	Polyurethane

Temperatures:

Temperature °C (short term):	-40 ... 120 °C
Temperature °C (continuous):	-40 ... 80 °C
Temperature °F (short term):	-40 ... 250 °F
Temperature °F (continuous):	-40 ... 175 °F

Accessories:

MPS ARCA 3020	Mounting plate (250x150x2 mm)
---------------	-------------------------------

MPP ARCA 3020	Mounting plate perforated (250x150x2 mm - 26x11 mm)
MPMP ARCA 3020	Mounting plate multiperforated (250x150x2 mm - □3.6 mm)
MPX ARCA 3020	Mounting plate (250x150 mm)
DRS ARCA 302015	DIN rail frame set
DRS ARCA 302021	DIN rail frame set
IDS ARCA 3020	Inner door set
PMK ARCA 20	Pole mounting kit
RCS ARCA 3020	Rain canopy set
SBK ARCA 20	Support bar kit
SBK ARCA 30	Support bar kit

Rating:

- Ingress Protection (EN 60529): IP65
- Impact Resistance (EN 62262): IK08
- Electrical insulation: Totally insulated
- Halogen free (DIN/VDE 0472, Part 815): 1
- Flammability Rating: UL 94 5VA
- Glow Wire Test (IEC 695-2-1) °C: 960
- NEMA Class: NEMA 4, 4X, 12 and 13

Certificates:
SGS Fimko

