



Bit set with Torque screwdriver

0.05-0.6 Nm 46 pcs

Item no.	4-930
Designation	Bit set with Torque screwdriver 0.05-0.6 Nm 46 pcs including bits + bit adapter 1/4 inch to 4 mm + extension 115 mm
Specification	adjustable torque, tolerance +/-6%.
Tightening torque	0.05-0.6 Nm / 5-60 cNm / 0.51-6.1 KgdcM / 0.4-5.3 in-lb
Connection	Hex Knurled screw, Lock function Clamping ball bit holder
Material	Aluminum, Steel Aluminum eloxed, steel Innickel-plated
Product packaging	Plastic case dimensions 175 x 160 x 45 mm

Dimensions and weight

socket length = 15 mm
 socket Ø = 10 mm
 total length 100 mm
 drive 1/4 Zoll (6,35 mm)
 weight 420 g



Application and technology

Each torque screwdriver is unit tested and certified according to DIN ISO 6789 / ASME B107.300-2010 torque standard (certificate enclosed).

CARE AND MAINTENANCE: To ensure tolerance, calibration must be performed regularly, recommended calibration interval is at least every 12 months. The product is lubricated for a lifetime of use, and should not require additional oiling.

IMPORTANT NOTE: When not in use, return the torque screwdriver to its original position (0 Nm). This relieves the preload and prevents premature wear. At best, always put back in the box after use to keep dirt and moisture out.

Set the desired torque and lock it with the black knurled screw. When the set torque is reached, you should hear an audible click and feel it engage. If this is not the case, please readjust the small screw on the screwdriver slightly so that the screwdriver clicks audibly. Never disassemble the torque screwdriver yourself. Repairs should only be carried out by a qualified service station. An improper repair attempt may result in damage and the accuracy requirements of DIN ISO 6789 and ASME 8107.300-2010 will then no longer be met.

Parts list

Bit set with torque screwdriver consists of:

4-563-100 Mini Torque Screwdriver 5-60cNm (0.05-0.6Nm) hex Drive 1/4

6-340-1 ESD bit holder dissipative for 4mm (5/32 inch) hex bits

6-340-2 bit extension for 4mm (5/32 inch) hex bits

6-340-3 C4 Bit set 42 pcs, consists of:

Slot 1.0-1.5-2.0-2.5-3.0

Cross-recess PH000-PH00-PH0-PH1

Torx T3-T4-T5-T6-T7-T8-T9-T10-T15

Hex 0.9-1.3-1.5-2.0-2.5-3.0

Wrench 2.5-3.0-3.5-4.0-4.5-5.0

Triangle 1.6-2.0-2.2-2.3, Square S0-S1

Pentalobe P2-P5-P6, SIM-Eject, Tri-Point 0-1

4-564 bit Adapter 1/4 to 4mm bits, length 42.5mm