



Section A-A



Section B-B



Section C-C

T 4000 - S F B A J 0 0 0 R

- |   |  |  |
|---|--|--|
| 1. PRODUCTS:<br>T:Terminal  | 5. MATERIAL:<br>B:Brass  | 7. WIRE OPTION:<br>I:Suitable For<br>22-26 Awg |
| 2. SERIES NO.:<br>4000  | 6. TERMINAL OPTION:<br>A:Female Terminal for<br>1x1P-1x14P/2x1P-2x7P | J:Suitable For<br>22-28 Awg                    |
| 3. CONTACT PLATING:<br>T: Tin<br>S: Selective Gold<br>G: Gold Flash | B: Female Terminal for<br>1x15P-1x30P/2x8P-2x29P                     | 8. FILL IT WITH "0"                            |
| 4. CONTACT TYPE:<br>F: Female                                       |  | 9. FILL IT WITH "0"                            |
|   |  | 10. FILL IT WITH "0"                           |
|   |  | 11. R: ROHS                                    |

Specifications & Ordering Information:

Part No	Thickness	Material	Wire Range	Insulation O.D.	Finish	Qty/reel
T4000-SFBAJ000R	0.2	Brass	AWG #22~28	1.6-1.2 mm	Selective Gold Flash	10,000PCS
T4000-TFBAJ000R	0.2	Brass	AWG #22~28	1.6-1.2 mm	Pre. Tin-Plated	10,000PCS

RoHS Compliant	<b>HSM</b> 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	SCALE 比例 参考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE : .000 : ±0.08 .00 : ±0.13 .0 : ±0.25
DWG. 製圖 BETTY		DATE 制表日 2009/08/14
PART NAME 品名 DUPOND 2.54mm TERMINAL BRASS MATERIAL SUITABLE AWG22-28 1R=10K PCS STANDARD TYPE (less than 1X14P & 2X7P use this type)		PART NO. 料號 T4000-XFBAJ000R