



SECTION A-A

GENERAL INFORMATION

- SECTION B-B
1. Lens material-Optical PC
  2. Operating Temperature rang; (40 to +100)deg.Upper limit ; +130 deg
  3. Storage tempereture range; (40 to +100)deg.Upper limit; +130 deg.
- Average transmittance in visible spectrum 400nm-700nm > 90%
- Usage and Maintenance
1. If necessary ,clean lenses with mild soap,water and soft cloth.
  2. Never use any commercial cleaning solvents like alcohol.
  3. Handel and install lenses with wearing gloves.
  4. skin oils may damage lenses or its optical characteristics

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 9001:2015 Class M3 and applies if not otherwise shown in the drawing.

ALL DIMENSIONS ARE IN MM  
COMMON TOLERANCE :- ± 0.15

		DEBURE & BREAK SHARP EGGES	DO NOT SCALE DRAWING		REVISION	REMARK.
	NAME	SIGNATURE	DATE	OPTIKS MECHATRONICS INDIA PVT.LTD		
DRAWN	ABHISHT		14-09-2022	PART NAME	28X1_3535_30°	
CHECKED	DEVESH		14-09-2022	DRAWING NUMBER	OMPL-548_REV00	
APPROVED	Pradyumna shandilya		14-09-2022.	PART NUMBER	OMPL-548_3535_30°	
MATERIAL		POLYCARBONATE		SCALE :		
WEIGHT		35.4 Gms		FIRST ANGLE PROJECTION		

This Drawing Is a Property Of Optiks Mechatronics Pvt.Ltd. It May Not Be Copied Or Otherwise Distributed Without Written Permission